


Specification Sheet

Part Number: 111-01235



Extreme temperature range for excellent performance in a range of environments.

Low-profile, contoured head takes up less space and protects sensitive wires.

Delivers the performance of a metal tie with the ease of use of plastic.

High-Temp Cable Tie, 8.7" Long, 85lb Tensile Strength, PEEK, Beige, 100/pkg

Article Number	111-01235
Type	PT220
Color	Beige (BGE)
Quantity Per	bag
Product Description	PEEK Ties withstand temperatures from -67 to 464 degrees F and provide excellent resistance to chemicals, acids, radiation and abrasion. The low-profile, contoured head takes up less space and protects sensitive wires running adjacent to it.
Short Description	High-Temp Cable Tie, 8.7" Long, 85lb Tensile Strength, PEEK, Beige, 100/pkg
Global Part Name	PT220-PEEK-BGE

Minimum Tensile Strength (Imperial)	85.0
Minimum Tensile Strength (Metric)	380.0
Length L (Imperial)	8.7
Length L (Metric)	220.0
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.19
Width W (Metric)	4.7
Bundle Diameter Min (Imperial)	0.32
Bundle Diameter Min (Metric)	8.0
Bundle Diameter Max (Imperial)	2.2
Bundle Diameter Max (Metric)	56.0
Thickness T (Imperial)	0.05
Thickness T (Metric)	1.3

Cable Tie Head Length (Imperial)	0.28
Cable Tie Head Width (Imperial)	0.32
Material	Polyetheretherketone (PEEK)
Material Shortcut	PEEK
Flammability	UL 94 V-0
Halogen Free	Yes
UV Resistant (Yes/No)	No
Operating Temperature	-67°F to +464°F (-55°C to +240°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	Lloyd's Register IEC 62275 DNV GL EN 62275:2009 IEC EN 62275
Package Quantity (Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)