

Cable - CAB-M104CFM/OE/22/S/ 1M - 2909789

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Assembled shielded round cable; connection 1: Single wires (49-position) (The wires are marked and fitted with ferrules. The braided shield is routed to a separate cable end.); connection 2: Connector (1x 104-position); cable length: 1 m

Your advantages

- Individual wire marking: 1, 2, 3, 4, etc.
- Individual wires fitted with ferrules
- Open end at one end
- AMP M-Series connector at one end

Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
GTIN	 4 055626 682808
GTIN	4055626682808

Technical data

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

General

Max. permissible operating voltage	125 V AC
	125 V DC
Max. current carrying capacity per path	2 A

Cable

Length of cable	1 m
Type of cable	Assembled shielded round cable
Single wire, cross section	0.36 mm ²
Single wire, cross section [AWG]	22
External cable diameter	14.1 mm
Shielding	yes
	Overall foil and braid shield

Cable - CAB-M104CFM/OE/22/S/ 1M - 2909789

Technical data

Cable

Halogen-free cable	No
--------------------	----

Connection data

Connection name	Field level
Connection method	Connector
Number of connections	1
Number of positions	104

Connection data 2

Connection name	Controller level
Connection method	Single wires
Number of positions	49
Note	The wires are marked and fitted with ferrules. The braided shield is routed to a separate cable end.

Supported controller

Controller	APACS
------------	-------

Color code

Connector 1 = connector 2 (optional) = wire color	M104CFM (1) = black
	M104CFM (3) = white
	M104CFM (5) = red
	M104CFM (6) = green
	M104CFM (8) = orange
	M104CFM (10) = blue
	M104CFM (11) = white-black
	M104CFM (13) = red-black
	M104CFM (14) = green-black
	M104CFM (16) = orange-black
	M104CFM (17) = blue-black
	M104CFM (19) = black-white
	M104CFM (21) = red-white
	M104CFM (22) = green-white
	M104CFM (24) = blue-white
	M104CFM (27) = black-red
	M104CFM (36) = white-red
	M104CFM (41) = orange-red
	M104CFM (43) = blue-red
	M104CFM (44) = red-green
	M104CFM (45) = orange-green
	M104CFM (46) = black-white-red
	M104CFM (47) = white-black-red
	M104CFM (49) = red-black-white

Cable - CAB-M104CFM/OE/22/S/ 1M - 2909789

Technical data

Color code

	M104CFM (56) = green-black-white
	M104CFM (57) = orange-black-white
	M104CFM (64) = blue-black-white
	M104CFM (65) = black-red-green
	M104CFM (70) = white-red-green
	M104CFM (71) = red-black-green
	M104CFM (72) = green-black-orange
	M104CFM (73) = orange-black-green
	M104CFM (74) = blue-white-orange
	M104CFM (75) = black-white-orange
	M104CFM (78) = white-red-orange
	M104CFM (79) = orange-white-blue
	M104CFM (84) = white-red-blue
	M104CFM (85) = black-white-green
	M104CFM (90) = white-black-green
	M104CFM (91) = red-white-green
	M104CFM (92) = green-white-blue
	M104CFM (94) = orange-red-green
	M104CFM (95) = blue-red-green
	M104CFM (96) = black-white-blue
	M104CFM (98) = white-black-blue
	M104CFM (100) = red-white-blue
	M104CFM (101) = green-orange-red
	M104CFM (102) = orange-red-blue
	M104CFM (104) = blue-orange-red

Classifications

eCl@ss

eCl@ss 10.0.1	27242220
eCl@ss 11.0	27242220
eCl@ss 9.0	27242220

Accessories

Accessories

Marker carrier cable

Cable - CAB-M104CFM/OE/22/S/ 1M - 2909789

Accessories

Cable marker carrier - KME - 0807083



Cable marker carrier, white, unlabeled, mounting type: Assembly with cable binders, cable diameter: > 5 mm, lettering field size: 20 mm x 8 mm

Phoenix Contact 2021 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>