

.XX ±0.13


.XXX ±0.05


10.70

5.80









THIS SERIES FULLY CONFORMS TO

THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

Ľ

J

COMPLIANT

## NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, GOLD FLASH PLATED
OPERATING TEMPERATURE:	-55°C ~ 125°C
POWER/CO-AX CONTACT RATING: (IF PRESENT)	30A (CURRENT)
SIGNAL CONTACT CURRENT RATING	
SIGNAL CONTACT RESISTANCE:	10mΩ MAX.
INSULATOR RESISTANCE:	5000MΩ min.
DIELECTRIC	
WITHSTANDING VOLTAGE:	1000V AC rms

COMBINATION D-SUB		SW REFERENCE NO.: 630 COMBO ASSEMBLY		
		DRAWN: C.B	DATE: JAN. 01/2019	
		CHECKED:	DATE:	
EDAC INC TORONTO, ONTARIO CANADA EDAC INC TORONTO, ONTARIO CANADA EDAC INC TORONTO, ONTARIO CANADA EDAC INC TORONTO, ONTARIO OR USED AS THE BASIS FOR THE		SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2
	DRAWING NUMBER: 630-11W	1250-3T3	ISSUE	
YOUR CONNECTION TO QUALITY & SERVICE MANUFACTURE OR SALE OF AP WITHOUT WRITTEN PERMISSION		PART NUMBER: 630-11W	1250-3T3	1

