HMIDT75XFH

EXtreme touchscreen panel, Harmony GTUX, 15 W Display full coated



Main	
Range of Product	Harmony GTUX
Product or Component Type	EXtreme touchscreen panel
Terminal type	Touchscreen display
[Us] rated supply voltage	12 V DC power supply
Supply voltage limits	10.828.8 V
Power consumption in W	12.5 W
Inrush current	30 A

Complementary

Complementary		
Touchscreen resolution	1024 x 1024	
Pixel resolution	1366 x 768	
Display size	15.6 inch	
Aspect ratio	4:3	
Display type	Colour TFT LCD	
Display Resolution	1366 x 768 pixels FWXGA	
Display colour	262144 colors	
Luminance	92.90 fc (1000 cd/m²)	
Touch panel	Single touch analogue resistive	
Type of cooling	Natural convection	
Cut-out dimensions	394 (+ 1/- 0) x 250 (+ 1/- 0) mm	
Width	16.06 in (408 mm)	
Height	10.39 in (264 mm)	
Depth	2.68 in (68 mm)	
Net Weight	10.58 lb(US) (4.8 kg)	

Environment

Environment		
IP degree of protection	IP66f	
	IP67f	
	Front panel Type 4X	
Standards	UL 61010	
	UL 121201	
	CSA C22.2 No 213	
	CSA C22.2 No 61010-1	
	IEC 61132-2	
Product Certifications	KC	
	CE	
	RCM	
	EAC	
	ATEX zone 2/22	
	IEC-Ex	
	UL	
	CSA	
Ambient air temperature for operation	-4140 °F (-2060 °C) EN 61131-2	
Ambient air temperature for storage	-4140 °F (-2060 °C)	
Pollution degree	2	
Environmental characteristic	3C3	
	UV resistant	
Relative Humidity	1090 % non-condensing	

Operating altitude	6561.68 ft (2000 m)
Vibration resistance	3.5 mm 59 Hz) EN/IEC 61131-2 9.8 m/s² 9150 Hz) EN/IEC 61131-2
Shock resistance	392 m/s ² EN/IEC 61131-2
Electromagnetic compatibility	Electrostatic discharge immunity testlevel 3 EN/IEC 61000-4-2

Ordering and shipping details

Category	22567-MAGELIS HMI GTU	
Discount Schedule	MC2	
GTIN	3606481572943	
Nbr. of units in pkg.	1	
Package weight(Lbs)	13.80 lb(US) (6.261 kg)	
Returnability	No	

Packing Units

r doming of mo	
Unit Type of Package 1	PCE
Package 1 Height	16.69 in (42.4 cm)
Package 1 width	6.89 in (17.5 cm)
Package 1 Length	20.75 in (52.7 cm)
Unit Type of Package 2	BB1
Number of Units in Package 2	1
Package 2 Weight	13.80 lb(US) (6.261 kg)
Package 2 Height	16.73 in (42.5 cm)
Package 2 width	6.81 in (17.3 cm)
Package 2 Length	20.67 in (52.5 cm)
Unit Type of Package 3	P12
Number of Units in Package 3	16
Package 3 Weight	240.69 lb(US) (109.176 kg)
Package 3 Height	43.31 in (110 cm)
Package 3 width	31.50 in (80 cm)
Package 3 Length	47.24 in (120 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

