




THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.














NOTES:

MATERIAL:

HOUSING: THERMOPLASTIC POLYESTER, UL94V-0 SHELL: STEEL, TIN PLATED CONTACT: COPPER ALLOY, 15µ GOLD PLATED OPERATING TEMPERATURE: -55°C to +85°C

CURRENT RATING: 3A PER CONTACT CONTACT RESISTANCE: 25mQ MAX. INSULATOR RESISTANCE: 5000MΩ min. DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC rms

				SW REFERENCE NO.: 628 ASSEMBLY		
	628 SERIES D-SUB CONNECTOR		DRAWN: C.B	DATE: AUG. 01/20	018	
			CHECKED: DATE:		ĨE:	
	EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: 1:1	SHEET 1 OF	1	
YOUR CC	TORONTO, ONTARIO CANADA		DRAWING NUMBER: 628-009-	.321-253	ISSUE	
	YOUR CONNECTION TO QUALITY & SERVICE		PART NUMBER: 628-009-	321-253	1	



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.