

## Specification Sheet

Part Number: 155-32602



Connector Clip w/Fir Tree, 0.75 - 5.0 mm Panel Thickness, 6.5 - 7.0 mm Hole Dia, PA66HIRHS, Black, 500/pkg

**Article Number**

155-32602

**Type**

FT6LG.M.St.Aufn.II

**Color**

Black (BK)

**Features & Benefits**

- Head design contains clamping rails to provide full circumferential compression around bundles.
- Bent tail allows for quick insertion into head.

**Quantity Per**

bag

**Product Description**

Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

**Short Description**

Connector Clip w/Fir Tree, 0.75 - 5.0 mm Panel Thickness, 6.5 - 7.0 mm Hole Dia, PA66HIRHS, Black, 500/pkg

**Global Part Name**

FT6LG.M.St.Aufn.II-PA66HIRHS-BK

**Fixation Method**

Fir Tree

**Panel Thickness Min(Imperial)**

0.03

**Panel Thickness Max(Imperial)**

0.2

**Panel Thickness Min (Metric)**

0.75

**Panel Thickness Max (Metric)**

1.5

**Mounting Hole Diameter D (Imperial)**

0.26 - 0.28

**Mounting Hole Diameter D (Metric)**

6.5 - 7.0 mm

**Mounting Hole Diameter D Min (Imperial)**

0.26

**Mounting Hole Diameter D Max (Imperial)**

0.28

**Mounting Hole Diameter D Max (Metric)**

7.0

**Disc Diameter(Metric)**

16

**Disc Diameter (Imperial)**

0.63

**Material**

Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

**Material Shortcut**

PA66HIRHS

**Flammability**

UL 94 HB

**Operating Temperature (Metric)**

-40°F to +221°F (-40°C to +105°C)

**Reach Complaint(Article 33)**

Yes

**ROHS Complaint**

Yes

**Package Quantity(Imperial)**

500

**Package Quantity (Metric)**

500

**Customs Number**

3926909988

**Content Unit(BMEcat)**

pcs.

**Weight (Metric)**

0.8