

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

| P | LTR | DESCRIPTION   | DATE      | DWN | APVD |
|---|-----|---------------|-----------|-----|------|
|   | A   | INITIAL       | 17APR2015 | DW  | CW   |
|   | B   | ECR-15-018270 | 09DEC2015 | DW  | CW   |
|   | B1  | ECR-16-018198 | 27DEC2016 | QY  | CW   |
|   | C   | ECR-21-111798 | 22SEP2021 | WQR | CW   |

TYPE-1:T2111020201-000 TE LOGO  
 类型-1:T2111020201-000 TE LOGO

NOTES:

1. TECHNICAL CHARACTERISTICS:  
 INSULATION MATERIAL: PC  
 RATED VOLTAGE: 1000V  
 RATED CURRENT: 70A  
 INSULATION RESISTANCE:  $\geq 400M\Omega$   
 RATED IMPULSE VOLTAGE: 8KV  
 POLLUTION DEGREE: 3  
 FLAMMABILITY: UL94V-0  
 MATING CYCLES: 500 CYCLES  
 WIRE RANGE: 10~25 mm<sup>2</sup>  
 CONTACT TYPE: CRIMP CONTACT

2. CONTACT NEED TO BE ORDERED SEPARATELY.  
 (ORDER No. REFER TO DRAWING:T2400002XX0000)

注释:

1. 技术参数:  
 绝缘材料: PC  
 额定电压: 1000V  
 额定电流: 70A  
 绝缘电阻:  $\geq 400M\Omega$   
 额定脉冲电压: 8KV  
 污染等级: 3  
 阻燃等级: UL94V-0  
 插拔次数: 500次  
 接线范围: 10~25 mm<sup>2</sup>  
 接线类型: 冷压接

2. 端子需要单独订购。  
 (订货号参考图面: T2400002XX0000)

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:  
mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

|        |    |
|--------|----|
| 0 PLC  | ±- |
| 1 PLC  | ±- |
| 2 PLC  | ±- |
| 3 PLC  | ±- |
| 4 PLC  | ±- |
| ANGLES | ±- |
| FINISH | -  |

MATERIAL

-

-

DWN 17APR2015

David Wang

CHK 17APR2015

Chris Wang

APVD 17APR2015

Xiang Xu

PRODUCT SPEC

108-137059

APPLICATION SPEC

114-137059

WEIGHT

-

Customer Drawing

TE Connectivity

NAME

HMN-002-FC

SIZE

A3

CAGE CODE

00779

DRAWING NO

T2111020201000

RESTRICTED TO

-

SCALE

3:2

SHEET

1 OF 2

REV

C

1470-19 (3/13)

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

REVISIONS

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

| P | LTR | DESCRIPTION | DATE | DWN | APVD |
|---|-----|-------------|------|-----|------|
| - |     | SEE SHEET 1 | -    | -   | -    |
|   |     |             |      |     |      |
|   |     |             |      |     |      |

NOTES:  
SEE SHEET 1

注释:  
见页 1

TYPE-2: T2111020201-001 NO LOGO  
类型-2: T2111020201-001 NO LOGO

ALL DIMENSIONS ARE SAME AS TYPE 1,  
EXCEPT THOSE DEFINED IN THIS TYPE.  
除了在本类型中定义的尺寸外, 其它尺寸同类型 1

| T2111020201-001   | HMN-002-FC             | HMN-002 FEMALE MODULE INSERT, CRIMPING, NO LOGO<br>HMN-002 冷压型模块母插, 无LOGO | TYPE-2<br>类型-2 |
|-------------------|------------------------|---|----------------|
| T2111020201-000   | HMN-002-FC             | HMN-002 FEMALE MODULE INSERT, CRIMPING<br>HMN-002 冷压型模块母插                 | TYPE-1<br>类型-1 |
| PART NUMBER<br>料号 | PART DESCRIPTION<br>描述 |   | TYPE<br>类型     |

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN 17APR2015

David Wang

CHK 17APR2015

Chris Wang

APVD 17APR2015

Xiang Xu

PRODUCT SPEC

108-137059

APPLICATION SPEC

114-137059

WEIGHT

-

Customer Drawing

TE Connectivity

NAME

HMN-002-FC

SIZE

A3

CAGE CODE

00779

DRAWING NO

G-T2111020201000

RESTRICTED TO

-

SCALE

3:2

SHEET

2

OF

2

REV

C

DIMENSIONS:

mm

TOLERANCES UNLESS  
OTHERWISE SPECIFIED:

|        |    |
|--------|----|
| 0 PLC  | ±- |
| 1 PLC  | ±- |
| 2 PLC  | ±- |
| 3 PLC  | ±- |
| 4 PLC  | ±- |
| ANGLES | ±- |

MATERIAL

-

FINISH

-

1470-19 (3/13)