

R413R333050T0K

Aliases (413R333050T0K)

R41T, Film, Metallized Polypropylene, Automotive Safety, 0.33 uF, 10%, 300 VAC (Y2), 125°C, Lead Spacing = 27.5mm



Click here for the 3D model.

Dimensions	,
L	32mm +0.3/-0.7mm
Н	28mm +0.1/-0.7mm
Т	14mm +0.2/-0.7mm
S	27.5mm +/-0.4mm
LL	25mm +2/-1mm
F	0.8mm +/-0.05mm

Packaging Specifications		
Packaging	Tray	
Packaging Quantity	176	

General Information			
Series	R41T		
Dielectric	Metallized Polypropylene		
Style	Radial		
Features	Automotive Grade, EMI Safety		
RoHS	Yes		
Lead	Wire Leads		
Safety Class	Y2		
Qualifications	AEC-Q200, ENEC, UL, cUL, CQC		
AEC-Q200	Yes		
THB Performance	Yes		
Component Weight	14.7 g		

Specifications			
Capacitance	0.33 uF		
Capacitance Tolerance	10%		
Voltage AC	300 VAC (Y2)		
Temperature Range	-40/+125°C		
Rated Temperature	125°C		
Dissipation Factor	0.3% 1KHz		
Insulation Resistance	100 GOhms		
Max dV/dt	400 V/us		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.