



Plug-in miniature power relay, With power contact, 1 CO contact, Input voltage: 60 VDC

Business data

<u>15503.2</u>
PRC 1/60V DC
4044211118167
10
PC
5 g
6.38 g
G
85364900
ES
Plug-in relay





Technical data	
Dimensions	
Length	28 mm
Width	5 mm
Height	15 mm
Ratings	
Overvoltage category	III
Contamination degree	3 (250 VAC) / 2 (400 VAC)
Input data	
Working voltage	42-90 VDC -
Holding current	0,4 Un -
Drop-out voltage	0,05 Un
Coil voltage	60 VDC -
Power consumption	0,176 W
Coil resistance	20500 Ohm
Output data	
Switching voltage / switching voltage max.	250 / 400 VAC
Continuous current max. / Inrush current max.	6 / 10 A
Contact configuration	1 CO contact
Switching capacity, max.	1500 VA
Electrical lifespan (AC1)	60x10 ³
Mechanical lifespan	10x10?
Contact load, min.	500 mW
Bounce time at close of the NO/NC contact	3/8 ms
Materials	
Contact material	AgNi
Working temperature, min.	-40 °C
Working temperature, max.	85 °C
Further technical data	
Degree of protection	RTIII (wash-tight)
Insulation voltage coil/contact	4 kV
Response/release time	12 / 5 ms
Insulation voltage contact/contact	1 kV
Vibration resistance NO/NC	10/5 g
Shock resistance NO/NC	10/5 g





Technical data	
Environmental Product Compliance	
REACH Conform	yes
REACH Reference date	2022-01-17
REACH Candidate Substance Note	No
RoHS Conform	yes







Approvals	
Standards and regulations	
CE compliant	





Media





15503.2 PRC 1/60V DC



Accessories

##INVERSE##CONTA-ELECTRONICS



Interface-Relay-Compact (IRC) socket base IRC with screw connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 110 to 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16191.2	IRC 110125V AC/DC	4044211187279	10 ST



Interface-Relay-Compact (IRC) socket base FIRC with Push-In connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 110 to 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16211.2	FIRC 110125V AC/DC	4044211187460	10 ST



Interface-Relay-Compact (IRC) socket base FIRC P with Push-In connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 60 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16214.2	FIRCP 60V AC/DC	4044211187491	10 ST



Interface-Relay-Compact (IRC) socket base FIRC P with Push-In connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 110 to 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16215.2	FIRCP 110125V AC/DC	4044211187514	10 ST



Interface-Relay-Compact (IRC) socket base FIRC P with Push-In connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 230 to 240 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16216.2	FIRCP 230240V AC	4044211187507	10 ST



Interface-Relay-Compact (IRC) socket base FIRC P with Push-In connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 110 to 125 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16217.2</u>	FIRCP 110125V DC	4044211187521	10 ST



##INVERSE##CONTA-ELECTRONICS



Interface-Relay-Compact (IRC) socket base IRCI with screw connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 110 to 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16202.2	IRCI 110125V AC/DC	4044211187392	10 ST



Interface-Relay-Compact (IRC) socket base IRCO with screw connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 230 to 240 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16206.2	IRCO 230240V AC	4044211187439	10 ST



Interface-Relay-Compact (IRC) socket base FIRC P with Push-In connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 220 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
16218.2	FIRCP 220V DC	4044211187538	10 ST



Interface-Relay-Compact (IRC) socket base FIRC P with Push-In connection and residual current suppression for long cables, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 110 to 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16219.2	FIRCP LW 110125V AC/DC	4044211187545	10 ST



Interface-Relay-Compact (IRC) socket base FIRC P with Push-In connection and residual current suppression for long cables, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 230 to 240 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16220.2	FIRCP LW 230240V AC	4044211187552	10 ST



Interface-Relay-Compact (IRC) socket base FIRC I with Push-In connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 110 to 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16222.2	FIRCI 110125V AC/DC	4044211187576	10 ST

15503.2 PRC 1/60V DC



##INVERSE##CONTA-ELECTRONICS



Interface-Relay-Compact (IRC) socket base FIRC I with Push-In connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 230 to 240 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16223.2	FIRCI 230240V AC	4044211187583	10 ST



Interface-Relay-Compact (IRC) socket base FIRC O with Push-In connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 110 to 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16225.2	FIRCO 110125V AC/DC	4044211187606	10 ST



Interface-Relay-Compact (IRC) socket base IRC with screw connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 230 to 240 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16192.2	IRC 230240V AC	4044211187286	10 ST



Interface-Relay-Compact (IRC) socket base IRCP with screw connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 60 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16194.2	IRCP 60V AC/DC	4044211187309	10 ST



Interface-Relay-Compact (IRC) socket base IRCP with screw connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 110 to 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16195.2	IRCP 110125V AC/DC	4044211187316	10 ST



Interface-Relay-Compact (IRC) socket base IRCP with screw connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 230 to 240 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16196.2	IRCP 230240V AC	4044211187323	10 ST



Interface-Relay-Compact (IRC) socket base IRCI with screw connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 230 to 240 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16203.2	IRCI 230240V AC	4044211187408	10 ST



##INVERSE##CONTA-ELECTRONICS



Interface-Relay-Compact (IRC) socket base IRCO with screw connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 110 to 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16205.2	IRCO 110125V AC/DC	4044211187422	10 ST



Interface-Relay-Compact (IRC) socket base FIRC with Push-In connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 230 to 240 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16212.2	FIRC 230240V AC	4044211187477	10 ST



Interface-Relay-Compact (IRC) socket base FIRC O with Push-In connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 230 to 240 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16226.2	FIRCO 230240V AC	4044211187613	10 ST



Interface-Relay-Compact (IRC) socket base IRCP with screw connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 110 to 125 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
16197.2	IRCP 110125V DC	4044211187347	10 ST



Interface-Relay-Compact (IRC) socket base IRCP with screw connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 220 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
16198.2	IRCP 220V DC	4044211187354	10 ST



Interface-Relay-Compact (IRC) socket base IPRC with screw connection and residual current suppression for long cables, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 110 to 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16199.2	IRCP LW 110125V AC/DC	4044211187361	10 ST

Data sheet 15503.2 PRC 1/60V DC



##INVERSE##CONTA-ELECTRONICS



Interface-Relay-Compact (IRC) socket base IPRC with screw connection and residual current suppression for long cables, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 230 to 240 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16200.2	IRCP LW 230240V AC	4044211187378	10 ST