

www.lemo.com

# PCA.0S.650.CTLC32Z

### **SUMMARY**

#### # Wires

 Low
 0

 High
 0

 Coax
 0

Triax 1
Quad 0

Fiber 0

Fluidic 0

Series OS

**Termination type** Female solder

IP rating 50

**Cable Ø** 2.30 - 3.20 mm

**Status** active

Alternative part

Matching parts FFA.0S.650.CTAC32Z



Image is for illustrative purpose only

#### **Download**

Request a quote

Catalog

### **TECHNICAL DETAILS**

#### **Mechanics**

Shell Style/Model PCA\*: Free receptacle, cable collet and nut for fitting a bend relief

Keying

Housing Material Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces

Variant Z: Nut for fitting a bend relief

Weight 9.60 g

#### **Performance**

Configuration 0S.650 : 1 Triax (50 Ohm)

Insulator T: PTFE Rated Current 6 Amps

#### **Specifications**

Contact Type: Triaxial 50 Ohm (Solder)

Max. Matings: 1000

Contact Dia.: 0.9 mm (0.035"in) Vtest: 1200 V (AC), 1700 V (DC)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Impedance: 50 Ohm VSWR: 1.03 + 0.34 \* f/GHz Cable type: RGT 178, RGT 174

#### **Others**

Endurance (Shell): 5000 mating cycles Temp (min / max): -55°C / +250°C


Humidity (max): <=95% [at 60 deg C /140 F]

Vibration: 15 g [10 Hz - 2000 Hz] Shock Resistance: 100 g [ 6 ms] Climatical Category: 50/175/21 Shielding (min): 75 dB (10 MHz) Shielding (min): 40 dB (1 GHz) Salt Spray Corrosion: >144 hr

IP Rating: 50

## **DRAWINGS**

#### **Draws**







#### **Dimensions**

	А	L	S2
mm.	8.9	33.5	7
in.	0,35	1,32	0,28

# **RECOMMENDED BY LEMO**

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

#### **Tools**

Spanner wrench: DCD.0S.005.PA065

#### **Cables**

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.