

\searrow	13	12	11	10	9	8	7	
J	PART NO.	ENGINEE	RING ND. F	FINISHED LE	ENGTH			
	1201080173	E11A0630	5M006 (),6M [1′8″]				
	1201080174	E11A0630)5M010 2	LOM [3'3"]				
	1201080179	E11A0630)5M100 (1	10,0M [32'10"				











NOTES:

Н

G

F

Е


D

C

- 1. MATERIAL: AS NOTED
- 2. FINISH: AS NOTED
- 3. ELECTRICAL: VOLTAGE: 30V CURRENT: 1.5A
- 4. TEMP RATING: -20° TO +75°C
- 5. PROTECTION: IP67 (WHEN MATED)
- 6. COUPLING THREAD: M12 X 1
- 7. UL CERTIFIED FILE: E200650
- 8. ALL DIMS ARE FOR REFERENCE UNLESS NOTED OTHERWISE

в							CAD /06	QUALITY SYMBOL	GENERAL TOLE (UNLESS SPE		DIMENSION STYLE	SCALE	DESIGN UNITS		ANGLE CTION	B
	7	WRAP LABEL		VINYL	BLACK/YELLOW) A-(8/09 8/10		mm		DRAWN BY DATE	TITLE				-
	6	□∨ERMOLD		PBT	GRAY		N TC 201	< I 🖤	4 PLACES ±	±	RSTONE 2018/09/0		12 D-CODED		_	
	5	COUPLING NUT		BRASS	NICKEL PLATEI		AWN 011' MAN		3 PLACES ±	<u>±</u>	CHECKED BY DATE		4P 90D MAL			
	4	SHIELD HOUSING		BRASS	NICKEL PLATED) REDRAWN 32019-0111 TONE 20 CHRAST (OODMAN20		2 PLACES ±		C CHRAST	- <u> </u>	-CODE 24AV	VG, 360 SHL	LU	-
A	3	CONTACT PIN		COPPER ALLOY	GOLD PLATED		D R CHI CHI	5 ·	1 PLACE ±	<u> </u>	BWOODMAN 2018/10/0	1 molex	MOLEX INC	ORPORATE	Ð	
	2	MALE INSERT, D-CODE	-	PUR	BLACK) AND): IPG: V: RST): C C 2: C C				MATERIAL NO.	DOCUMENT N	IO.		SHEET NO.	Δ
	1	CABLE, 2 PAIR, 26AW	/G, SHLD	TPE JACKET	TEAL		REVD EC NO DRWN CH'KD APPR		DRAFT WH APPLICAI				SD-120108-0		1 0F 1	
	ITEM	DESCRIPTION		MATERIAL	FINISH		<u>в В</u>		MUST REN WITHIN DIME	/IAIN			ORMATION THAT IS P IOT BE USED WITHO			
	13	3 12	11	10	9	8		7	6	5	4	3	2		1	

6	5	4	3 2		1	
		>. .3 .9 1.4 3. 7. 14	ABLE LENGTH T 3M [1FT]: +19mm 9M [1 - 3FT]: +4 - 1.8M [3 - 6FT]: - 8 - 3.7M [6 - 12FT 7 - 7.3M [12 - 24F 3-14.6M [24 - 48F 6 - 30.5M [48-10 VER 30M [100FT]	-0 [+.75in-0] 44.5mm-0 [+1.75i +55.6mm-0 [+2.19 7 +88.9mm-0 [+3. 7]: +165.1mm-0 7]: +317.5mm-0 0 FT]: +622.3mm-	9in-0] .50in-0] [+6.50in-0] [+12.50in-0] 0 [+24.50in-0]	J J



(B)							
REF,	THIS	DRAWING	SUPERSEDES	CO-CREATE	DDC	SD-120108-038	REV-1