







(1)





NOTES:

MATERIAL: HOUSING: SHELL: CONTACT: **OPERATING TEMPERATURE:**


STEEL, NICKEL PLATED COPPER ALLOY, 30µ GOLD PLATED

.XX ±0.13


.XXX ±0.05

POWER/CO-AX CONTACT RATING: 40A (CURRENT) (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX.

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:



| | | | SW REFERENCE NO.: 630 COMBO ASSEMBLY | | |
|--|--|---------------------------------|--------------------------------------|-------|--|
| COMBINATION D-SUB | | DRAWN: C.B | DATE: JAN. 01/20 | 19 | |
| | | CHECKED: | DATE: | | |
| EDAC INC TORONTO, ONTARIO CANADA YOUR CONNECTION TO QUALITY & SERVICE | THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION. | SCALE: (IN C.A.D. 1:1) | SHEET 1 OF | 2 | |
| | | DRAWING NUMBER: 630-21W1640-4N5 | | ISSUE | |
| | | PART NUMBER: 630-21W | 1640-4N5 | 1 | |





THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.



5000MΩ min.

1000V AC rms

-55°C ~ 125°C

THERMOPLASTIC POLYESTER, UL94V-0

