

N	0	TΕ	S:

(IF PRESENT)

DIELECTRIC

INSULATOR RESISTANCE:

WITHSTANDING VOLTAGE:

MATERIAL:
HOUSING:
SHELL:
CONTACT:
OPERATING TEMPERATURE:

-55°C ~ 125°C POWER/CO-AX CONTACT RATING: 20A (CURRENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX.


STEEL, TIN PLATED

THERMOPLASTIC POLYESTER, UL94V-0

COPPER ALLOY, 30µ GOLD PLATED



1000V AC rms



	COMBINATION D-SUB		SW REFERENCE NO.: 630 COMBO ASSEMBLY			
COMBINATIO			DATE: JAN. 01/2019			
			DATE:			
EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2		
		DRAWING NUMBER: 630-3W3-650-2TB		ISSUE		
YOUR CONNECTION TO QUALITY & SERVICE		PART NUMBER: 630-3W3	-650-2TB	1		



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.



