



ADVANCED CABLE TIES PART NUMBER	BUNDLE DIAMETER		A IN (mm) +/- .250 (6.350mm)	B IN (mm) +/- .250 (6.350mm)	C IN (mm) +/- .010 (.254mm)	D IN (mm) +/- .020 (.508mm)	E IN (mm) +/- .010 (.254mm)	MIN LOOP TENSILE LBS (n)	ANSI/UL 94 MH FLAMABILITY RATING	
	MIN IN (mm)	MAX IN (mm)								
AP(R,L)-05-50-RL-#	.390 (10.0mm)	1.59 (40.386mm)	5.875 (149.22mm)	5.180 (131.572mm)	.290 (7.594mm)	.302(7.670mm)	.059 (1.498mm)	50 (222)	V-2	
**AP(R,L)-07-50-RL-#	.062 (1.57mm)	1.875 (47.625mm)	7.562 (192.075mm)	6.375 (161.925mm)	.180(4.572mm)	.215 (5.461mm)	.052(1.320mm)	50 (222)	V-2	
AP(R,L)-08-50-RL-#	.390 (10.0mm)	2.19 (55.626mm)	7.875 (200.025mm)	7.063 (179.400mm)	.290 (7.594mm)	.312(7.924mm)	.059 (1.498mm)	50 (222)	V-2	
**AP(R,L)-11-50-RL-#	.062 (1.57mm)	3.062 (77.775mm)	11.250 (285.751mm)	10.125 (257.175mm)	.180(4.572mm)	.215 (5.461mm)	.052(1.320mm)	50 (222)	V-2	
AP(R,L)-12-50-RL-#	.390 (10.0mm)	3.47 (88.138mm)	11.875 (301.625mm)	11.063 (281.000mm)	.290 (7.594mm)	.312(7.924mm)	.059 (1.498mm)	50 (222)	V-2	
**AP(R,L)-14-50-RL-#	.062 (1.57mm)	4.000 (101.600mm)	14.35 (364.49mm)	13.225 (335.915mm)	.180(4.572mm)	.215 (5.461mm)	.052(1.320mm)	50 (222)	V-2	
						<b>50 LB. (222n) RELEASABLE CABLE TIES</b>				
F	9/7/21	DW	DW	RB	UPDATED B DIMENSIONS					
E	3/7/18	PB	EG	EG	UPDATED UL SPECS AND ADDED VENDOR SPECS					
D	3/6/18	PB	EG	EG	DIMENSION A +/- FROM .125 TO .250, DIMENSION C +/- FROM .005 to .010 AND 14-50-RL DIMENSION A FROM 14.250 TO 14.35					
C	4/29/17	JA	KT	KT	NEW LOGO ADDED					
B	7/26/16	JA	KT	KT	ADDED 7, 11 & 14-50		<b>COLOR DESIGNATIONS:</b> # 0 = UV BLACK 9 = NATURAL 30 = HEAT STABILIZED			
A	12/22/14	JA	KT	KT	INITIAL RELEASE		<b>MATERIAL:</b> <b>NYLON 6/6 POLYAMIDE</b>			
REV	DATE	BY	CHK	APPROVE	DESCRIPTION	J A	7/26/16	CHECK	SCALE	
								KT	NONE	

**CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.**  
**THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.**

SPC-4.10.59.6