

R413I2680JH00K

Aliases (413I2680JH00K)

R41, Film, Metallized Polypropylene, Automotive Safety, 0.068 uF, 10%, 300 VAC (Y2), 1000 VDC, 110 °C, Lead Spacing = 15mm



Click here for the 3D model.

Dimensions	l e e e e e e e e e e e e e e e e e e e
L	18mm +0.3/-0.5mm
Н	19mm +0.1/-0.5mm
Т	11mm +0.2/-0.5mm
S	15mm +/-0.4mm
LL	3.2mm +0.3/-0.2mm
F	0.8mm +/-0.05mm

Packaging Specifications	
Packaging	Bulk, Bag
Packaging Quantity	450

General Information				
Series	R41			
Dielectric	Metallized Polypropylene			
Style	Radial			
Features	Automotive Grade, EMI Safety			
RoHS	Yes			
Lead	Cut			
Safety Class	Y2			
Qualifications	AEC-Q200, ENEC, UL, cUL, CQC			
AEC-Q200	Yes			
THB Performance	No			
Component Weight	5.1 g			

Specifications	
Capacitance	0.068 uF
Capacitance Tolerance	10%
Voltage AC	300 VAC (Y2)
Voltage DC	1000 VDC
Temperature Range	-40/+110°C
Rated Temperature	110°C
Dissipation Factor	0.2% 1kHz
Insulation Resistance	100 GOhms
Max dV/dt	600 V/us

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.