

R49AW447040B1M

Aliases (49AW447040B1M)

R49, Film, Metallized Polypropylene, Safety, 4.7 uF, 20%, 330 VAC (X1), 800 VDC, 110 °C, Lead Spacing = 37.5 mm



Click here for the 3D model.

Dimensions	,
L	41.5mm +0.3/-0.7mm
Н	40mm +0.1/-0.7mm
Т	19mm +0.3/-0.7mm
S	37.5mm +/-0.4mm
LL	30mm +5mm
F	1mm +/-0.05mm

Packaging Specifications	,
Packaging	Tray
Packaging Quantity	96

General Information		
Series	R49	
Dielectric	Metallized Polypropylene	
Style	Radial	
Features	EMI Safety	
RoHS	Yes	
Lead	Wire Leads	
Safety Class	X1	
Qualifications	ENEC, UL, cUL	
AEC-Q200	No	
THB Performance	No	
Component Weight	39.84 g	

Specifications	
Capacitance	4.7 uF
Capacitance Tolerance	20%
Voltage AC	330 VAC (X1)
Voltage DC	800 VDC
Temperature Range	-40/+110°C
Rated Temperature	110°C
Dissipation Factor	0.1% 1kHz
Insulation Resistance	6.383 GOhms
Max dV/dt	100 V/us

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.