



Henkel Corporation

Digi-Key Corp.
701 Brooks Ave S
Thief River Falls, MN 56701-2757
United States

Date: 08/25/2021

Dear Valued Customer:

Enclosed please find a new or revised Safety Data Sheet(s) (SDSs). You are receiving this/these in accordance with country/regional regulatory requirements.

<u>Item Number</u>	<u>IDH Number</u>	<u>Product Description</u>
1188076	1188076	LOCTITE STYCAST 2651MM UNP known as STYCAST 2651MM Unpig (12lb),

Previous versions of these documents should be replaced by the newer version.

SDSs should be forwarded to personnel responsible for workplace safety and to employees who will be handling this/these product(s) to ensure awareness and understanding of safety concerns and regulatory responsibilities. SDSs must also be forwarded on to your customers if you further distribute or resell the product.

If you have any questions, please contact your local Product Safety and Regulatory Affairs Specialist.

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

For Safety Data Sheet updates please visit our website
<https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

Sincerely,

Henkel Product Safety and Regulatory Affairs

Safety Data Sheet



Revision Number: 004.0

Issue date: 03/18/2020

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE STYCAST 2651MM UNP known as STYCAST 2651MM Unpig (12lb),
Product type/use: Epoxy resin
Restriction of Use: None identified
Company address: Henkel Corporation
One Henkel Way
Rocky Hill, Connecticut 06067

IDH number: 1188076

Item number: 1188076
Region: United States

Contact information:
Telephone: +1 (860) 571-5100
MEDICAL EMERGENCY Phone: Poison Control Center
1-877-671-4608 (toll free) or 1-303-592-1711
TRANSPORT EMERGENCY Phone: CHEMTREC
1-800-424-9300 (toll free) or 1-703-527-3887
Internet: www.henkeln.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: CAUSES SKIN IRRITATION.
MAY CAUSE AN ALLERGIC SKIN REACTION.
CAUSES SERIOUS EYE IRRITATION.
SUSPECTED OF CAUSING GENETIC DEFECTS.
SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.
CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
GERM CELL MUTAGENICITY	2
REPRODUCTIVE TOXICITY	2
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	1

PICTOGRAM(S)



Precautionary Statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapors, mist, or spray. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face protection.

Response: IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.

Storage: Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

IDH number: 1188076

Product name: LOCTITE STYCAST 2651MM UNP known as STYCAST 2651MM Unpig (12lb),
Page 1 of 6

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Limestone	1317-65-3	30 - 60
Epoxy resin	Proprietary	30 - 60
butyl glycidyl ether	2426-08-6	1 - 5
Magnesium carbonate	546-93-0	1 - 5
Quartz (SiO ₂) respirable particulates (RCS) >=10%	14808-60-7	1 - 5

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. If symptoms develop and persist, get medical attention. Wash clothing before reuse.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Ingestion:	Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray.
Unusual fire or explosion hazards:	Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.
Hazardous combustion products:	Oxides of carbon. Irritating vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Ensure adequate ventilation. Isolate area. Keep unnecessary personnel away. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

7. HANDLING AND STORAGE

Handling:	Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Refer to Section 8.
Storage:	For safe storage, store at or below 25 °C (77°F) Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Limestone	10 mg/m ³ TWA Total dust.	5 mg/m ³ PEL Respirable fraction. 15 mg/m ³ PEL Total dust.	None	None
Epoxy resin	None	None	None	None
butyl glycidyl ether	3 ppm TWA (SKIN) (Dermal sensitization)	50 ppm (270 mg/m ³) PEL	None	None
Magnesium carbonate	None	5 mg/m ³ PEL Respirable fraction. 15 mg/m ³ PEL Total dust.	None	None
Quartz (SiO ₂) respirable particulates (RCS) >=10%	0.025 mg/m ³ TWA Respirable fraction.	0.05 mg/m ³ TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m ³ OSHA_ACT (Respirable dust.) 0.05 mg/m ³ PEL Respirable dust. 2.4 MPPCF TWA Respirable. 0.1 mg/m ³ TWA Respirable.	None	None

Engineering controls:

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Respiratory protection:

Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.

Eye/face protection:

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	Off white
Odor:	Slight
Odor threshold:	Not available.
pH:	Not available.
Vapor pressure:	< 0.1 mm hg (25 °C (77°F)) None
Boiling point/range:	Not determined
Melting point/ range:	Not applicable
Specific gravity:	1.65
Vapor density:	> 1.0
Flash point:	> 93.3 °C (> 199.94 °F) no method
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	Not determined
Solubility in water:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
VOC content:	Negligible
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	Oxides of carbon. Irritating vapors.
Incompatible materials:	Strong oxidizing agents. Strong acids. Amines.
Reactivity:	Not available.
Conditions to avoid:	Store away from incompatible materials. Heat, flames, sparks and other sources of ignition.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation:	May cause respiratory tract irritation. In a confined area, high concentrations of vapors may cause headache, nausea, and dizziness. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release.
Skin contact:	Causes skin irritation. May cause allergic skin reaction.
Eye contact:	Causes serious eye irritation.
Ingestion:	May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Limestone	None	Nuisance dust
Epoxy resin	None	Allergen, Irritant
butyl glycidyl ether	Oral LD50 (Rat) = 2,000 mg/kg Oral LD50 (Rat) = 2.05 g/kg Oral LD50 (Mouse) = 1.53 g/kg Dermal LD50 (Rabbit) = 0.788 g/kg	Irritant, Allergen, Central nervous system, Liver, Mutagen
Magnesium carbonate	None	Gastrointestinal, Immune system, Irritant
Quartz (SiO ₂) respirable particulates (RCS) >=10%	None	No Data

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Limestone	No	No	No
Epoxy resin	No	No	No
butyl glycidyl ether	No	No	No
Magnesium carbonate	No	No	No
Quartz (SiO ₂) respirable particulates (RCS) >=10%	Known To Be Human Carcinogen.	Group 1	Yes

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.
Hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s. (Epoxy resin)
Hazard class or division: 9
Identification number: UN 3082
Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)
Hazard class or division: 9
Identification number: UN 3082
Packing group: III
Marine pollutant: Epoxy resin

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.
TSCA 12 (b) Export Notification: None above reporting de minimis
CERCLA/SARA Section 302 EHS: None above reporting de minimis.
CERCLA/SARA Section 311/312: Immediate Health, Delayed Health
CERCLA/SARA Section 313: None above reporting de minimis.
California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2,3,8,11,16

Prepared by: Product Safety and Regulatory Affairs
Issue date: 03/18/2020

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.