## ATGBICS AFBR-79EEPZ-IF1 Avago Broadcom Compatible Transceiver QSFP+ 40GBase-CSR4 (850nm, MMF, 400m, MTP/MPO, DOM)

Brand : ATGBICS

Performance

Interface type \*

Wavelength

Ethernet LAN

(DDM)

(WDM)

Features

Product colour

Plug and Play Hot-Plug support

Easy to install

Country of origin

Hot-swap

Housing material

SFP transceiver type \* Maximum data transfer rate \*

Fiber optic connector

SFP transceiver standard

Ethernet interface type

**Digital Diagnostics Monitoring** 

Wavelength-division multiplexing

Maximum transfer distance

Single-mode fiber (SMF) supported

Multi-mode fiber (MMF) supported

Product code: AFBR-79EEPZ-IF1-C

Product name : AFBR-79EEPZ-IF1 Avago Broadcom Compatible Transceiver QSFP+ 40GBase-CSR4 (850nm, MMF, 400m, MTP/MPO, DOM)

AFBR-79EEPZ-IF1 Avago Broadcom Compatible Transceiver QSFP+ 40GBase-CSR4 (850nm, MMF, 400m, MTP/MPO, DOM)

ATGBICS AFBR-79EEPZ-IF1 Avago Broadcom Compatible Transceiver QSFP+ 40GBase-CSR4 (850nm, MMF, 400m, MTP/MPO, DOM):

ATGBICS AFBR-79EEPZ-IF1 40GBase-SR4 supports a distance of up to 400m over multi mode fibre (MMF) using a wavelength of 850nm via an MPO connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of AFBR-79EEPZ-IF1= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.

Fiber optic

QSFP+

×

1

MPO

400 m

850 nm

40 Gigabit Ethernet

SR

1

J

×

Silver

Metal

1

1


1

United Kingdom

40000 Mbit/s

## Features Brand compatibility Avago Technologies Certification CE, FCC, RoHS Power Input voltage 3.3 V Maximum voltage 3.5 V **Operational conditions** 70 °C Maximum operating temperature Operating temperature (T-T) 0 - 70 °C Storage temperature (T-T) -40 - 85 °C Operating relative humidity (H-H) 0 - 95% Storage relative humidity (H-H) 0 - 95% Weight & dimensions Width 13.5 mm Depth 72.4 mm Height 18.4 mm Weight 42 g Packaging data Number of products included 1 pc(s) Package type Box **Technical details** Sustainability compliance 1 RoHS Sustainability certificates Doesn't contain Lead





5056468752819

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.