
## **BGA Heat Sink - High Performance Straight Fin w/Thermal Tape**





ATS Part#: **ATS-54270K-C1-R0** 

Description: 27.00 x 27.00 x 14.50 mm BGA Heat Sink - High Performance Straight Fin

w/Thermal Tape

Heat Sink Type: Straight Fin
Heat Sink Attachment: Thermal Tape

Equivalent Part Number: ATS-54270K-C2-R0

\*Image above is for illustration purpose only.

## **Features & Benefits**

- High aspect ratio, straight fin heat sinks that are ideal for compact PCB environments
- · Designed specifically for BGAs and other surface mount packages
- · Comes preassembled with high performance thermal interface material

## **Thermal Performance**

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	7.6 °C/W	5.9 °C/W	5.1 °C/W	4.6 °C/W	4.2 °C/W	3.9 °C/W	3.7 °C/W
	Ducted Flow	4.5	N/A	N/A	N/A	N/A	N/A	N/A

## **Product Detail**

Schematic Image Dimension		Dimension B	Dimension C	Dimension D	TIM	Finish
	27.00 mm	27.00 mm	14.50 mm	N/A mm	T412	BLACK-ANODIZED
*Image above is for illustration purpose only.	<ul> <li>Dimension</li> <li>ATS-5427 (Saint-Go</li> <li>Thermal papplication</li> <li>ATS reserved</li> <li>ATS certifies</li> </ul>	70K-C2-R0 is the exbain C675). Derformance data aren. The right to update. The right to update. The right to the right to update. The right to the right to update.	height from the botto	bly with an equivalence only. Actual penducts without notices	ent thermander rformander e to impr	al interface material e may vary by



