


C941U332MUVDBAWL40

Not for New Design

C900AH SFTY X1-400 Y1-250, Ceramic, 3300 pF, 20%, 400 VAC (X1), 250 VAC (Y1), Y5V, Lead Spacing = 10mm



Click here for the 3D model.

Dimensions	
D	11mm MAX
т	5.5mm MAX
S	10mm +/-1mm
LL	4mm +/-1mm
F	0.55mm +/-0.1mm

Packaging Specifications

Packaging	Bulk, Bag
Packaging Quantity	500

General Information	
Series	C900AH SFTY X1-400 Y1-250
Style	Radial Disc
RoHS	Yes
Termination	Tin
Failure Rate	N/A
Qualifications	UL, ENEC, VDE, CSA, CAN
AEC-Q200	No
Halogen Free	Yes
Component Weight	1g

Specifications			
Capacitance	3300 pF		
Capacitance Tolerance	20%		
Voltage AC	400 VAC (X1), 250 VAC (Y1)		
Dielectric Withstanding Voltage	4000 VDC		
Temperature Range	-40/+125°C		
Temperature Coefficient	Y5V		
Dissipation Factor	5%		
Insulation Resistance	10 GOhms		
Safety Class	X1/Y1		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.