

# Housing - HC-STA-D07-CHWSCF-1TTM20-EL-AL - 1419243

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Coupling housings D7, with single locking latch, material: Die-cast aluminum, salt water resistant, cable outlets: 1, straight, height: 60.5 mm, cable gland: none, support sleeve: yes, 1x M20, Standard, for socket inserts



## Key Commercial Data

|              |               |
|--------------|---------------|
| Packing unit | 1 pc          |
| GTIN         |               |
| GTIN         | 4055626159744 |

## Technical data

### Dimensions

|        |         |
|--------|---------|
| Height | 60.5 mm |
| Width  | 34.2 mm |
| Length | 24.2 mm |

### Ambient conditions

|                                 |                   |
|---------------------------------|-------------------|
| Degree of protection (IP)       | IP66              |
|                                 | IP67              |
| Ambient temperature (operation) | -40 °C ... 125 °C |

### General

|                      |   |
|----------------------|---|
| Note                 | for contact inserts HC-A03, A04, D07, D08, Q02, Q03, Q04, Q05, Q07, Q12 |
| Size                 | D7  |
| Housing type         | Coupling housings   |
| Color                | gray aluminum   |
| Locking type         | with single locking latch   |
| No. of cable outlets | 1   |
| Cable outlet         | straight  |

# Housing - HC-STA-D07-CHWSCF-1TTM20-EL-AL - 1419243

## Technical data

### General

|                              |   |
|------------------------------|---|
| Screw connection             | none                                    |
| Type of the screw connection | 1x M20                                  |
| Housing material             | Die-cast aluminum, salt water resistant |
| Housing surface material     | uncoated                                |

### Environmental Product Compliance

|            |   |
|------------|---|
| China RoHS | Environmentally Friendly Use Period = 50  |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

## Approvals

### Approvals

---

#### Approvals


EAC / DNV GL

---

#### Ex Approvals

---

### Approval details

|     |   |                          |
|-----|---|--------------------------|
| EAC |  | RU C-<br>DE.AI30.B.01102 |
|-----|---|--------------------------|

|        |   |   |            |
|--------|---|---|------------|
| DNV GL |  | <a href="https://approvalfinder.dnvgl.com/">https://approvalfinder.dnvgl.com/</a> | TAE000037S |
|--------|---|---|------------|

Phoenix Contact 2019 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
 Flachsmarktstr. 8  
 32825 Blomberg  
 Germany  
 Tel. +49 5235 300  
 Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>