



# **Product Description**

Security & Commercial Audio Cable, Plenum-CMP 2-22 AWG stranded bare copper conductors with Flamarrest® insulation, Flamarrest® jacket with ripcord

## **Technical Specifications**

#### Product Overview

Suitable Applic	cations:	Security System, Intercom/PA, Audio/Speaker, Noisy Environment						
onstructio	on Details							
onductor								
Element	Number of Element	Size	Stranding	Material				
Conductor(s)	2	22 AWG	7x30	BC - Bare Coppe	r			
sulation					-			
Element	Material	Nom	n. Thickness	Nom. Insulatio	n Diameter	Color Code		
Conductor(s)	PVC - Polyvinyl Chlor	ride 0.008	3 in (0.20 mm)	) 0.045 in (1.1 mr	n)	Black, Red		
uter Jacket								
Materi	al Nom. Th	ickness	Nom. Diam	eter Ripcord				
VC - Polyviny			0.120 in (3.0					
verall Cable	Diameter (Nominal):	0.120 in (3	8.05 mm)					
lectrical C	Characteristics							
ectricals								
Element	Nom. Conductor DC	R Nom.	Capacitance	Cond-to-Cond	Мах	. Current		
Conductor(s)	16.9 Ohm/1000ft	55 pF/	'ft (180 pF/m)		6 Amps per (	Conductor at 25°C		
. ,	16.9 Ohm/1000ft	55 pF/	'ft (180 pF/m)		6 Amps per 0	Conductor at 25°C		
Conductor(s) Ditage JL Voltage Ra		55 pF/	'ft (180 pF/m)		6 Amps per (	Conductor at 25°C		
oltage JL Voltage Ra		55 pF/	ft (180 pF/m)		6 Amps per (	Conductor at 25°C		
oltage JL Voltage Ra	ating		ft (180 pF/m)		3 Amps per 6	Conductor at 25°C		
oltage JL Voltage Ra			ft (180 pF/m)		3 Amps per 6	Conductor at 25°C		
oltage JL Voltage Ra 300 V Iechanical emperature	ating I Characteristic	S			∂ Amps per (	Conductor at 25°C		
oltage JL Voltage Ra 300 V lechanical emperature JL Temperatu	ating I Characteristic	S			∂ Amps per (	Conductor at 25°C		
oltage JL Voltage Ra 300 V Iechanica	ating I Characteristic	S		(	∂ Amps per (	Conductor at 25°C		
oltage JL Voltage Ra 300 V lechanical emperature JL Temperatu	ating I Characteristic	S			∂ Amps per (	Conductor at 25°C		
Ditage JL Voltage Ra 300 V Iechanical emperature JL Temperatu 75°C	I Characteristic	S			∂ Amps per (	Conductor at 25°C		
Ditage JL Voltage Ra 300 V Iechanical emperature JL Temperature 75°C end Radius	ating I Characteristic ure Operating II 0°C to +75°C 0° n. Installation Min.	S			∂ Amps per (	Conductor at 25°C		
Ditage JL Voltage Ra 300 V Iechanical emperature JL Temperature JL Temperature so C end Radius Stationary Mil	ating I Characteristic ure Operating In 0°C to +75°C 0° n. Installation Min. 1.3 in (33 mm)	S	C		3 Amps per (	Conductor at 25°C		

Environmental Suitability:	Indoor - Plenum, Indoor
Flammability / Reaction to Fire:	NFPA 262, UL 910 (Plenum), FT6, IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 800, CMP
CEC / C(UL) Compliance:	CMP
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Non-Plenum Number:	5500UE

## History

Update and Revision:

Revision Number: 0.500 Revision Date: 05-01-2023

#### **Part Numbers**

#### Variants

ltem #	Color	Putup Type	Length	UPC
6500UE 8771000	Natural	Reel	1,000 ft	612825177449
6500UE 877C1000	Natural	Coil	1,000 ft	612825340409
6500UE 877U1000	Natural	UnReel	1,000 ft	612825420088
6500UE 877Z1000	Natural	ReelTuff Box	1,000 ft	612825177470
6500UE 007U1000	Violet	UnReel	1,000 ft	

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.