ATGBICS AFBR-57R6AEZ-HP3 Avago Broadcom Compatible Transceiver SFP+ 4.25/2.125/1.0625/1.25GBase-FC (850nm, MMF, 300m, DOM, Ext Temp)

Brand: ATGBICS Product code: AFBR-57R6AEZ-HP3-C



Product name : AFBR-57R6AEZ-HP3 Avago Broadcom Compatible Transceiver SFP+ 4.25/2.125/1.0625/1.25GBase-FC (850nm, MMF, 300m, DOM, Ext Temp)

AFBR-57R6AEZ-HP3 Avago Broadcom Compatible Transceiver SFP+ 4.25/2.125/1.0625/1.25GBase-FC (850nm, MMF, 300m, DOM, Ext Temp)

ATGBICS AFBR-57R6AEZ-HP3 Avago Broadcom Compatible Transceiver SFP+ 4.25/2.125/1.0625/1.25GBase-FC (850nm, MMF, 300m, DOM, Ext Temp):



ATGBICS AFBR-57R6AEZ-HP3 4.25/2.125/1.0625/1.25GBase-FC supports a distance of up to 300m over multi-mode fibre (MMF) using a wavelength of 850nm via an LC connector. This product can operate at extended temperatures between -10°C to 85°C. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of Avago Broadcom AFBR-57R6AEZ-HP3= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.

Performance		Power	
FP transceiver type * Fiber optic flaximum data transfer rate * 4250 Mbit/s flaximum data transfer rate * SFP+	4250 Mbit/s	Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 1 W
Single-mode fiber (SMF) supported Multi-mode fiber (MMF) supported Fiber optic connector SFP transceiver standard Maximum transfer distance Wavelength Ethernet LAN Ethernet interface type	LC SR 300 m 850 nm 10 Gigabit Ethernet	Operational conditions Minimum operating temperature Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-10 °C 85 °C -10 - 85 °C -40 - 85 °C 0 - 95% 0 - 95%
Digital Diagnostics Monitoring (DDM) Wavelength-division multiplexing (WDM)		Weight & dimensions Width Depth Height	13.4 mm 56.5 mm 8.5 mm
Features		Weight	19 g
Product colour Housing material Plug and Play Hot-Plug support	Silver Metal	Packaging data Number of products included Package type	1 pc(s) Box
Hot-swap Easy to install Country of origin Brand compatibility		Technical details Sustainability compliance Sustainability certificates Doesn't contain	✓ RoHS Lead
Certification	CE, FCC, RoHS	DOESH C CONCAIN	Leau



5056468769138

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.