


REVISIONS											
REV	ECO	DESCRIPTION	DATE	BY	APPR						
A1		RELEASED	16MAR2020	J. HEAD	DH						



NOTES: UNLESS OTHERWISE SPECIFIED

1. RECEPTACLE MATERIAL: SHELL: ZINC ALLOY, NICKEL PLATED INSERT AND RETAINING RING: THERMOPLASTIC


SEAL: SILICONE RUBBER


2. BACKSHELL MATERIAL:

SHELL: ALUMINIUM ALLOY, NICKEL PLATED; LATCH SEGMENT: ALUMINIUM ALLOY, NICKEL PLATED; SCREW AND LOCK WASHER: STAINLESS STEEL; BUSHING: EPDM.

3. SPECIFICATIONS:

- 3.1 OPERATING TEMPERATURE: -55°C TO +125°C.
- 3.2 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
- 3.3 INSULATION RESISTANCE: 1000 MEGOHM MIN @ 25°C.
- 3.4 MOISTURE RESISTANCE: IP67 & IP69K (MATED CONDITION).
- 3.5 MATING CYCLE DURABILITY: 100 CYCLES
- 3.6 RoHS COMPLIANT
- 4. APPLY BACKSHELL TO CABLE OD SIZE: Ø11.20-Ø19.30 . CAN BE USED WITH OR WITHOUT BUSHING.
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.
- 6. SEE SPECIFIC RECEPTACLE DRAWING FOR:
 - 6.1 CONTACT SIZE AND WIRE RANGE.
 - 6.2 RETAINING RING COLOR.
 - 6.3 MATING PART(S).
 - 6.4 CONTACT LAYOUT AND ALL OTHER SPECIFICATIONS.





	AHDM04-18-20SR-059			HD34-18-20SE-09	•			
	PART NUMBER			DESCRIPTION				ITEM
QUANTITY		MATERIALS LIST						
UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC ±0.30 Fractions ±1/64		SIGNATURES		DATE	Amphanal			
		DRAWN:	J. HEAD	16MAR2020	Amphenol			
2 PL DEC ±0.15 3 PL DEC ±0.08	Angles ±1°	CHECKED:			Sine Systems - www.amphenol-sine.com			
3) Note reference = 🛣 MATERIAL SPECIFICATIONS: PROCESS SPECIFICATIONS: NEXT ASSY:		ENGINEER:			44724 Morley Drive Clinton Township, MI 48036			
		APPROVAL:			- Clinton Township, MT 48036			
		CUSTOMER:			DURAMATE AHDM RECEPT, SIZE 18, WD THD,			
		SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO MORMAL		KIT V	V/ CABLE CLAMP I	BACKSHELL		
				B C-	AHDM04-18-2		A1	
				SCALE: NONE		SHEET 1 OF	1	

REV: A1 SH:

KIT, RECPT AND BACKSHELL, SZ 18