IPC ASSOCIATION CONNECTINE ELECTRONICS INDUSTRIES	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.				This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lowe level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.										
752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					rials and Mi	ials and Mfg Information				
upplier Inform	ation														
Company name*			Company unique ID			1	Unique ID Authority					Response Date*			
onsemi												2023-06-08			
Contact Name		Title - Contact			]	Phone - Contact*					Email - Contact*				
Product-Env-Stewa	rds		Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
uthorized Represe	ntative*	Title - Representative			]	Phone - Representative*				Email - Representative*					
Product-Env-Stewa	rds	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com					
Requeste	Requester Item Number Mfr Ite		em Number Mfr Item Name				Effective Dat	te Ve	ersion	Manufacturing Site		1	Weight*	UOM	Unit Type
		NCP1071	CP1071STBT3G High-Voltage Switch Offline SMPS; 100 k		tcher for Low kHz	Power	2023-06-08					1	09.99	mg	Each
Ianufacturing l	Proccess Information	n													
Terminal Plating / Grid Array Material To			Cerminal Base Alloy J-STD-020 MSL		L Rating	Peak Process Body Temperature   Max Time at 1		Time at Peak	Temperat	ure Num	ber of Reflow Cyc	eles			
Matte Tin (Sn) - annealed		C	CU Alloy 1				<b>260</b> C		30 seco		secon	ds 3			
omments															
vel 1 - maximum ti	ime at peak temperature	during sol	dering is 10-3	30 seconds											
or more informatio	on regarding material co	mposition 1	olease refer t	o page 3							· · · · · · · · · · · · · · · · · · ·				

RoHS Material Composition Declaration			Declaration Type *	Detail	ed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU  RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on informationprovided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the						

## **Homogeneous Material Composition Declaration for Electronic Products**

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	3.3	mg	Supplier	Silicon (Si)	7440-21-3		3.3	mg
Die Attach	2.37	mg	Supplier	Organic peroxide	3006-86-8		0.0178	mg
			Supplier	Diluent B	Proprietary Data		0.1185	mg
			Supplier	Diluent A	Proprietary Data		0.0948	mg
			Supplier	Dicyandiamine	461-58-5		0.0059	mg
			Supplier	Aluminum Trioxide (Al2O3)	1344-28-1		1.896	mg
			Supplier	Formaldehyde Polymer	9003-36-5		0.237	mg
Lead Frame	37.17	mg	Supplier	Silver (Ag)	7440-22-4		0.4832	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0372	mg
			Supplier	Iron (Fe)	7439-89-6		0.8921	mg
			Supplier	Copper (Cu)	7440-50-8		35.7575	mg
Mold Compound-Black	59.7	mg		Epoxy resin	proprietary data		2.985	mg
			Supplier	Phenolic Resin	Proprietary Data		2.985	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		1.194	mg
			Supplier	Carbon Black (C)	1333-86-4		0.2985	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		52.2375	mg
Plating	7.44	mg	Supplier	Tin (Sn)	7440-31-5		7.44	mg
Wire Bond - Au	0.01	mg	Supplier	Gold (Au)	7440-57-5		0.01	mg