[	т	۵	п	m			0	Φ	A	
4		Deault N	S-							4
ယ							LAYOUT SHO	VN AS EXAMPLE		3
			Keying Shown	as example						
	CHARACTERISTICS		Г	Connector dimension	_					
	-Standard : Based on MIL-DTL-38999	Series III	-	Dim Nominal						
2	-Shell Material : Aluminium   -Shell Plating : Black Zinc   -Insulator : Thermopla   -Contacts : Copper All   -Seals & Grommet : Silicon Elas   -Contact Plating : Gold over	Nickel Istic oy		ØS29.4 MaxZ31 MaxVV THREADM18x1-6g			due to a use of the Proo the Specifications issued by	Country Jurisdiction	with hird party	2
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories				PN: 8D513Z08AE					
	-Temperature Range : -65°C to +					A 19-10-2016	6 First Release			
	-Salt Spray : 500 hours -Mass : 21.42 g ± 1					ISS DATE	Latest modification - by		MOD	N°
						Designed By:	Date:	CU	STOMER DRAWING	
					TITLE	LE Aluminium Plug 8D series				
_	BASIC SERIES: SHELL TYPE : Plug with RFI Shieldin	8D 5 - 13 Z	08 A E			SCALE NA	General Tolera	nces:	NPRDS / PROJECT <b>859</b>	
	CONTACT TYPE : Standard Crimp (	Contact			IENTATION : E	SOURIAU	WWW.SOUR		This document is the property of SOURIAU it must not be reproduced or	
	CONTACT TYPE : PIN(500 Matings				communicated without permission					
	PLATING : Z = Black Zinc Nic	kel		CONTACT LA	AYOUT : 13-08			RIAU DRG N°	SHEE	
l	1	1			1	A3		13Z08AE-C	1/2	2
	H I	G	F	E \	T/	D	С	В	A	

		G	г П	m		0
		Contact Layout				
4		$x = \begin{bmatrix} e^{\Theta} & \Theta^{A} \\ e^{\Theta} & \Phi^{H} \\ e^{\Theta} & \Phi^{H} \\ e^{\Theta} & \Theta^{C} \\ e^{\Theta} $				
		Contacts (Insert arrangement 13-8)     Contact location     X-axis (mm)     X-axis (mm)     A   +.065 (1.65)   +.157 (3.99)     B   +.170 (4.32)   +.000 (0.00)     C   +.120 (3.05)  120 (3.05)     D  000 (0.00)  170 (4.32)     E  120 (3.05)  120 (3.05)     F  170 (4.32)   +.000 (0.00)     G  065 (1.65)   +.157 (3.99)     H   +.000 (0.00)   +.044 (1.12)				
ى ن	Shell Arrangement Nu size no. cr 13 -8	imber of Size Service Contact Supersede ontacts contacts rating location 8 20 I All MS20051-1				
						SOURIAU shall not be liable for an due to a use of the Products wl the Specifications issued by either o (professional recommenda
N						PN: 8D513
					A 19-10-20 ISS DATE Designed By:	16 First Release Latest modification - by Date:
					TITLE	Alumir General linear
<u> </u>					NA SOURIA	U WWW.SOURIAU.C
					FORMAT A3	SOURIAU 8D513Z
	Н	G	F	E	D	C

Φ						
		4				
		3				
any non-conformity or damage which does not comply with r of the Parties or by a third party dation, technical notice.)						
intry Juriso	Jurisdiction & Control List Not Listed					
3Z08AE						
		MOD N°				
	CUSTOMER DRAWING					
ninium Plug 8D series						
r	NPRDS / PROJECT 859					
	This document is the pr	operty of				
.COM	SOURIAU it must not be reprod communicated without p					
U DRG N° Z08AE-C		SHEET 2/2				
B	A					