



| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 66.3              |
| B   | 38.5              |
| C   | 55                |
| D   | 80                |

| NO. | BESCHREIBUNG / DESCRIPTION              |
|-----|---|
| 1   | ISOLIERKÖRPER STIFT / INSULATOR PIN     |
| 3   | DICHTKÖRPER / GROMMET                   |
| 5   | KONTAKTSTIFT/ CONTACT PIN               |
| 7   | ZYLINDERGHÄUSE / BARREL                 |
| 9   | ÜBERWURFMUTTER / COUPLING NUT           |
| 10  | DICHTRING FRONT / FRONT SEALING RING    |
| 11  | SCHIRMKRANZ/SHIELDING BRAID             |
| 16  | ENDGEHÄUSE GESCHIRMT / ENDBELL SHIELDED |

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Specification and Dimensions subject to change  
 Drawings illustrate normal insulator positioning

| Material Specification: |                                 |
|-------------------------|---------------------------------|
| Shell Material:         | Aluminium alloy                 |
| Shell Plating:          | Zinc cobalt, green (conductive) |
| Insulator Material:     | CR-Elastomere                   |
| Contact Material:       | Copper alloy                    |
| Contact Plating:        | Hard silver                     |

all dimensions are in mm  
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m  
 drawing for CUSTOMER

**ITT**  
*Engineered for life*  
 ITT CANNON GmbH  
 D - 71384 Weinstadt/Germany

description CA3106E36-3P-B-15-A233  
 Plug, straight shielded  
 Shielded with endbell for shielded braids & heat shrinkable boots  
 AWG Crimp / Pin / Layout: 36-3