

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

www.tripplite.com

# SmartRack 12U Mid-Depth Rack Enclosure Cabinet for Harsh Environments

# MODEL NUMBER: SR12UBFFD











Protects sensitive electronic equipment from harsh conditions that would overwhelm a typical rack enclosure. Ideal for use in factories, construction areas, utility plants, warehouses and other areas with limited space that are high in moisture, dust and debris. Fully compliant to IP54 standards.

# Description

This SmartRack 12U Mid-Depth Rack Enclosure Cabinet protects sensitive electronic equipment from harsh conditions that would overwhelm a typical rack enclosure. It is deal for use in factories, construction areas, utility plants, warehouses and other areas with limited space that are high in moisture, dust and debris. It can protect your equipment from falling dirt, dust, drips, splashes and accidental contact with personnel. On the front door there is a built-in dust filter. The filter is removable and can be replaced with standard furnace filters - they're simple, inexpensive and effective. To compensate for the added air resistance of the filters, there are 4 large, high performance intake fans in the front door. The fans pull air through the enclosure, from front to side. Adjustable rack rails with square mounting holes accommodate up to 12U of standard 19" rackmount equipment. Supports up to 1000 lbs of equipment.

#### **Features**

- 12U floor enclosure
- Protection from falling dirt, dust, drips, splashes and accidental contact with personnel
- Adjustable mounting depths from 3" to 32.5" inches
- Front door has ventilating louvers
- Built-in removable dust filter that can be replaced with standard furnace filters (20" x 24" x 1")
- 4 large, high-performance fans in front door that pull air through the enclosure, from front to rear
- 2 cable ports allow cable access while maintaining dust and moisture resistance
- Locking, reversible front door
- Locking, removable solid side panels
- Fully assembled for quick installation

## **Highlights**

- Built-In Dust Filter: Protects against airborne particles and easily replaced with standard off-the-shelf furnace filters
- Heavy-Duty Construction:
   Withstands jolts and vibrations
   in harsh working environments
- Louvered Door: Keeps out drips, splashing water and falling debris
- 4 High-Performance Fans:
   Maintain ample airflow to keep equipment cool

### **Package Includes**

- SmartRack 12U Mid-Depth
   Rack Enclosure Cabinet
- (36) M6 cagenuts
- (36) M6 screws
- (36) Washers
- (2) Keys
- (1) Removable/Replaceable dust filter
- (4) Casters
- (4) Leveling feet
- (1) C13 to NEMA 5-15 power cord, 10'
- Owner's Manual



 Meets all enclosure requirements towards PCI DSS (Payment Card Industry Data Security Standard) compliance

# **Specifications**

OVERVIEW		
UPC Code	037332183439	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Nominal Input Voltage Description	120V 50/60 Hz	
Input Plug Type	NEMA 5-15P	
Input Cord Length (ft.)	10	
Input Cord Length (m)	3.05	
PHYSICAL		
Rack Height	12U	
Maximum Device Depth (in.)	32.5	
Maximum Device Depth (cm)	82.55	
Minimum Device Depth (in.)	3	
Minimum Device Depth (cm)	7.62	
Shipping Dimensions (hwd / in.)	30.90 x 25.00 x 39.80	
Shipping Dimensions (hwd / cm)	78.49 x 63.50 x 101.09	
Shipping Weight (lbs.)	134.00	
Shipping Weight (kg)	60.78	
Unit Dimensions (hwd / in.)	25.2 x 23.6 x 38.5	
Unit Dimensions (hwd / cm)	64 x 59.95 x 97.79	
Unit Weight (lbs.)	96	
Unit Weight (kg)	43.54	
Color	Black	
Weight Capacity - Stationary (lbs.)	1000	
Weight Capacity - Rolling (lbs.)	1000	
Weight Capacity - Stationary (kg)	454	
Weight Capacity - Rolling (kg)	454	
Factory Preset Rack Depth (in.)	10.42	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

Factory Preset Rack Depth (cm)	26.5	
Factory Preset Rack Depth (mm)	265	
Maximum Device Depth (mm)	826	
Minimum Device Depth (mm)	76	
SPECIAL FEATURES		
Grounding Lug	Front and back door frames	
Built-in Cable Management	Yes	
CERTIFICATIONS		
Approvals	EIA-310-E, IEC 60297-3-100, IP54 Protection Rating, RoHS	
WARRANTY		
Product Warranty Period (Worldwide)	2-year limited warranty	

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>