

## Coupler connector - ST-08S1N8A9005S - 1619017

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Coupler connector, straight, SPEEDCON locking, M17, Number of positions: 8, Crimp connection, shielded: yes, Cable diameter: 10 mm...12.5 mm

The figure shows the 17-pos. product version

### Product Features

- Consistent EMC protection for reliable connection solutions in the industrial environment
- Crimping connection: vibration- and temperature-resistant assembly
- Flexible use: reliably connect various cable diameters



### Key Commercial Data

Packing unit	1 pc
Custom tariff number	85366990
Country of origin	Germany

### Technical data

#### General

Type of locking	SPEEDCON locking
Direction of rotation of contact chamber numbering	Standard
Coding	N
Contact connection method	Crimp connection
Number of positions	8
Contact diameter of power contacts	1 mm
Nominal current per power contact at 25°C	3.6 A
Conductor entry	10 mm ... 12.5 mm
Pg housing screw connection	none

#### Ambient conditions

Ambient temperature	-40 °C ... 125 °C
---------------------	-------------------

# Coupler connector - ST-08S1N8A9005S - 1619017

## Technical data

### Ambient conditions

Degree of protection	IP67
----------------------	------

### Specifications according to DIN EN 61984:2001

Installation height max.	3000 m
Nominal / operating voltage of power contacts	60 V
Rated surge voltage of power contacts	1.5 kV
Overvoltage category of power contacts	II
Degree of pollution of power contacts	3

## Classifications

### eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260702
eCl@ss 7.0	27440102
eCl@ss 8.0	27440102

### ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002635
ETIM 5.0	EC002635

### UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

## Approvals

### Approvals

---

### Approvals

cUL Recognized / UL Recognized / EAC / cULus Recognized

# Coupler connector - ST-08S1N8A9005S - 1619017

## Approvals

Ex Approvals

Approvals submitted

## Approval details

cUL Recognized	
Nominal current I <sub>N</sub>	5 A
Nominal voltage U <sub>N</sub>	60 V


UL Recognized	
Nominal current I <sub>N</sub>	5 A
Nominal voltage U <sub>N</sub>	60 V

EAC
-----

cULus Recognized
------------------

## Drawings

Schematic diagram



Connector pin assignment

Dimensional drawing

