

ATGBICS 371-1399-C network transceiver module Copper 1250 Mbit/s SFP

Brand : ATGBICS **Product code:** 371-1399-C

Product name: 371-1399-C



Sun Oracle Compatible Transceiver SFP 10/100/1000Base-T Copper RJ45 Connector 100m

ATGBICS 371-1399-C network transceiver module Copper 1250 Mbit/s SFP:

ATGBICS 371-1399 SFP operates on standard Category 5 unshielded twisted-pair copper cabling of link lengths up to 100m. Sun Oracle 1000BASE-T SFP modules support 10/100/1000 auto negotiation and auto MDI/MDIX. Our product is built to the exact specification of Sun Oracle 371-1399= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.

ATGBICS 371-1399-C. SFP transceiver type: Copper, Maximum data transfer rate: 1250 Mbit/s, Interface type: SFP. Product colour: Silver, Housing material: Metal, Country of origin: United Kingdom. Input voltage: 3.3 V, Maximum voltage: 4 V, Power consumption (typical): 1.3 W. Width: 13.4 mm, Depth: 56.6 mm, Height: 8.5 mm. Number of products included: 1 pc(s), Package type: Box



Performance		Features	
SFP transceiver type * Copper Maximum data transfer rate * 1250 Mbit/s Interface type * SFP Single-mode fiber (SMF) supported Multi-mode fiber (MMF) supported SFP transceiver standard Maximum transfer distance Ethernet LAN Ethernet interface type Copper ethernet cabling technology Auto MDI/MDI-X Digital Diagnostics Monitoring (DDM) Copper T250 Mbit/s SFP Copper Maximum transfer (SMF) supported X SFP Gigabit Ethernet 100 m Gigabit Ethernet 108ASE-TX,1008ASE-TX,10008ASE-TX X Digital Diagnostics Monitoring (DDM)	1250 Mbit/s SFP X TX	Brand compatibility	Oracle
		Power	
		Input voltage Maximum voltage Power consumption (typical)	3.3 V 4 V 1.3 W
		Operational conditions	
	Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	70 °C 0 - 70 °C -40 - 85 °C 5 - 85% 5 - 85%	
Features		Weight & dimensions	
Product colour Housing material Plug and Play	Silver Metal	Width Depth Height Weight	13.4 mm 56.6 mm 8.5 mm 24 g
Hot-Plug support Hot-swap		Packaging data	
Easy to install Country of origin		Number of products included Package type	1 pc(s) Box
		Technical details	
		Sustainability certificates	RoHS



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.