



- 1 PHOSPHOR BRONZE.
- 2 BRASS.
- 3 POLYPROPYLENE, GENERAL PURPOSE
- 4 ACETAL, GENERAL PURPOSE
- 5 TIN PLATE 2.54 μm [.000100] MINIMUM THICK.
- 6 NICKEL PLATE 2.54 μm [.000100] MINIMUM THICK.
- 7 CONNECTOR WILL ACCEPT CENTER CONDUCTOR DIAMETER RANGE OF 0.51[.020]-1.19[.047].

OBSOLETE

THIS DRAWING IS A CONTROLLED DOCUMENT.		DATE	VERSION	DESCRIPTION	DATE	QTY	PART NO
APPROVED BY: J. HAVENER		DATE	VERSION	DESCRIPTION	DATE	QTY	PART NO
DIMENSIONS: mm (inches)		OTHERS: OTHERS SPECIFIED:					
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APPROVED BY: J. HAVENER					
0 P.C. ± .005		DATE: 25MAR2017					
1 P.C. ± .005		VERSION: 1					
2 P.C. ± .005		DESCRIPTION: JACK, PCB, RIGHT ANGLE, F SERIES					
3 P.C. ± .005		DATE: 25MAR2017					
4 P.C. ± .005		VERSION: 1					
MATERIAL: SEE NOTES 1-4		WEIGHT: 0					
SEE NOTES 1-4		CUSTOMER DRAWING: A2 00779					
SEE NOTE 5 & 6		SCALE: 5:1					
CUSTOMER DRAWING		SIZE: A2					
		CODE: 00779					
		DRAWING NO: 5887078					
		RESTRICTED TO: -					
		SCALE: 5:1					
		SHEET: 1 of 1					
		REV: A1					

PCB CONFIGURATION

5887078-1
PART NUMBER

5887078