


## C951U332MUWDCA7317

Not for New Design

**General Information** 

Halogen Free

C900AH SFTY X1-400 Y1-250, Ceramic, 3300 pF, 20%, 400 VAC (X1), 250 VAC (Y1), Y5U, Lead Spacing =  $10 \, \mathrm{mm}$ 





The measurement position of Lead Spacing (S) and Width (V) is critical in straight lead capacitors.

	Series	C900AH SFTY X1-400 Y1-250
	Style	Radial Disc
t	RoHS	Yes
	Termination	Tin
11	Failure Rate	N/A
	Qualifications	UL, ENEC, VDE, CSA, CAN
	AEC-Q200	No

Yes

Specifications			
Capacitance	3300 pF		
Capacitance Tolerance	20%		
Voltage AC	400 VAC (X1), 250 VAC (Y1)		
Dielectric Withstanding Voltage	4000 VDC		
Temperature Range	-40/+125°C		
Temperature Coefficient	Y5U		
Dissipation Factor	2.5%		
Insulation Resistance	10 GOhms		
Safety Class	X1/Y1		

Click	here	for	the	3D	model
-------	------	-----	-----	----	-------

Dimensions				
D	12mm MAX			
Т	5mm MAX			
S	10mm +/-1mm			
НО	HO 18mm +2/-0mm			
F	0.55mm +/-0.1mm			

Packaging Specifications				
Packaging	Ammo			
Packaging Quantity	1000			

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.