Image is for illustrative purpose only



SUMMARY

Wires

 Low
 0

 High
 0

Coax 0

Triax 1

Quad 0 Fiber 0

Fluidic 0

Series OS

Termination type Female solder

IP rating 50

Cable Ø 2.30 - 3.20 mm

Status active

Alternative part

Matching parts FFA.0S.650.CTAC32

TECHNICAL DETAILS

Mechanics

Shell Style/Model *:

Keying

Housing Material Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces

Download

Catalog

Request a quote

Variant

Weight 8.75 g

Performance

Configuration 0S.650 : 1 Triax (50 Ohm)

Insulator T: PTFE Rated Current 6 Amps

Specifications

Contact Type: Triaxial 50 Ohm (Solder)

Max. Matings: 1000

Contact Dia.: 0.9 mm (0.035"in) Vtest: 1200 V (AC), 1700 V (DC)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Impedance: 50 Ohm VSWR: 1.03 + 0.34 * f/GHz Cable type: RGT 178, RGT 174

Others

Endurance (Shell): 5000 mating cycles Temp (min / max): -55°C / +250°C

Humidity (max): <=95% [at 60 deg C /140 F]

Vibration: 15 g [10 Hz - 2000 Hz] Shock Resistance: 100 g [6 ms] Climatical Category: 50/175/21 Shielding (min): 75 dB (10 MHz) Shielding (min): 40 dB (1 GHz) Salt Spray Corrosion: >144 hr

IP Rating: 50

DRAWINGS

Draws





Dimensions

RECOMMENDED BY LEMO

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Tools

Spanner wrench: DCD.0S.005.PA065

Cables

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.