




.XX ±0.13

.XXX ±0.05










## NOTES:

DIELECTRIC


WITHSTANDING VOLTAGE:

OPERATING TEMPERATURE:	-55°C ~ 125°C
MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, 30µ GOLD PLATED





1000V AC rms



	COMBINATION D-SUB			SW REFERENCE NO.: 630 COMBO ASSEMBLY			
				DRAWN: C.B		DATE: JAN. 01/2019	
			CHECKED:		DATE:		
	EDACINC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INCAND	SCALE: (IN C.A.D. 1	:1)	SHEET 1 OF	2	
		RONTO, ONTARIO CANADA	SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE	DRAWING NUMBER: 630-21W1640-3NE		ISSUE	
	YOUR CONNECTION TO QUALITY & SERV	ALITY & SERVICE	MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	PART NUMBER:	630-21W	1640-3NE	1



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

000000000000000000000000000000000000000

