




ĦĦ






1






## NOTES:

| MATERIAL:<br>HOUSING:<br>SHELL:<br>CONTACT:                  | THERMOPLASTIC POLYESTER, UL94V-0<br>STEEL, TIN PLATED<br>COPPER ALLOY, 30µ GOLD PLATED |        |
|--|--|--------|
| OPERATING TEMPERATURE:                                       | -55°C ~ 125°C  |        |
| POWER/CO-AX CONTACT RATING:<br>(IF PRESENT)                  | 20A (CURRENT)  | 7<br>7 |
| SIGNAL CONTACT CURRENT RATING:<br>SIGNAL CONTACT RESISTANCE: | 5A PER CONTACT<br>10mΩ MAX.  | 1      |
| INSULATOR RESISTANCE:<br>DIELECTRIC                          | 5000MΩ min.  | J      |
| WITHSTANDING VOLTAGE:  | 1000V AC rms   |        |



|                                      |  |                          | SW REFERENCE NO.: 630 COMBO ASSEMBLY |       |  |
|--------------------------------------|--|--------------------------|--------------------------------------|-------|--|
| COMBINATION D-SUB                    |  | DRAWN: C.B               | DATE: JAN. 01/20                     | 19    |  |
|                                      |  |                          | DATE:                                |       |  |
|                                      | THESE DRAWINGS AND SPECIFICATIONS<br>ARE THE PROPERTY OF EDAC INC.,AND<br>SHALL NOT BE REPRODUCED,OR COPIED<br>OR USED AS THE BASIS FOR THE<br>MANUFACTURE OR SALE OF APPARATUS<br>WITHOUT WRITTEN PERMISSION. | SCALE: (IN C.A.D. 1:1)   | SHEET 1 OF                           | 2     |  |
| TORONTO, ONTARIO<br>CANADA           |  | DRAWING NUMBER: 630-5W1- | -640-2TB                             | ISSUE |  |
| YOUR CONNECTION TO QUALITY & SERVICE |  | PART NUMBER: 630-5W1-    | -640-2TB                             | 1     |  |





THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.



.XX ±0.13

.XXX ±0.05

10.70

5.80

9.40

2.54

