

- > chrome nickel steel: stainless, anti-magnetic (18/10), very popular electronics quality
- > ESD coating: non-reflective black, with a surface resistance of approx. 10⁵ Ohm
- > tips non-reflective brushed
- > gripping surfaces matte finish for optimum grip

92 08 78 ESD

For SMD-technology*: bent tips; smooth gripping surfaces

92 08 79 ESD

Shaped to grip horizontal cylindrical components of 3/64" (1 mm) dia.; Smooth gripping surfaces; serrated handles

92 28 69 ESD

Straight tips; strong tip; smooth gripping surfaces

92 28 70 ESD

Straight tips; fine tip; smooth gripping surfaces

92 28 71 ESD

Needle-pointed tips; straight tips; smooth gripping surfaces

92 28 72 ESD

Solid; long tips; straight tips; smooth gripping surfaces

92 38 75 ESD

Sickle-shaped tips; smooth gripping surfaces

92 58 74 ESD



Round tips, approx. 5/64" (2 mm) wide; straight tips; smooth gripping surfaces

92 78 77 ESD

Round tips, approx. 9/64" (3.5 mm) wide; straight tips; serrated gripping surfaces; serrated handles

92 88 73 ESD

Rectangular tips, approx. 1/32" (0.9 mm) wide; gripping surfaces with fine transverse serration

**92 08 78 ESD****92 08 79 ESD****92 28 69 ESD****92 28 70 ESD****92 28 71 ESD****92 28 72 ESD****92 38 75 ESD****92 58 74 ESD****92 78 77 ESD****92 88 74 ESD**

Product Number	Packaging	↔ Inch mm		Finish	Δ lbs
92 08 78 ESD		4 3/4 120	✳️⚡️ 45°	stainless, anti-magnetic, electrically dissipative	0.04
92 08 79 ESD		4 3/4 120	✳️⚡️	stainless, anti-magnetic, electrically dissipative	0.04
92 28 69 ESD		5 1/8 130	✳️⚡️	stainless, anti-magnetic, electrically dissipative	0.04
92 28 70 ESD		4 1/4 110	✳️⚡️	stainless, anti-magnetic, electrically dissipative	0.03
92 28 71 ESD		4 1/4 110	✳️⚡️	stainless, anti-magnetic, electrically dissipative	0.04
92 28 72 ESD		5 1/4 135	✳️⚡️	stainless, anti-magnetic, electrically dissipative	0.05
92 38 75 ESD		4 3/4 120	✳️⚡️ 45°	stainless, anti-magnetic, electrically dissipative	0.04
92 58 74 ESD		4 3/4 120	✳️⚡️	stainless, anti-magnetic, electrically dissipative	0.04
92 78 77 ESD		5 3/4 145	✳️⚡️	stainless, anti-magnetic, electrically dissipative	0.06
92 88 73 ESD		5 1/8 130	✳️⚡️	stainless, anti-magnetic, electrically dissipative	0.04

* SMD-Technology: technique for soldering surface mounted components on printed circuit boards without using holes