

HDCM-4K 7" Ultra-Compact HD 4K Security Test Monitor

Connects using HDMI, Composite BNC-In & BNC-Out, and Component BNC

Features:

- 7" HD TFT LED LCD Monitor with 1920 x 1080P and 1.4 HDMI
- Connects using HDMI, Composite BNC-In/BNC-Out, and Component BNC
- AC powered or uses an externally mounted, easily swapped rechargeable battery with external battery charger
- Utilizes standard 7.4V 4400mAh 32.6Wh rechargeable battery
- Includes desk-, wall- or rack-mountable stand*, AC adapter, HDMI cable, rechargeable battery, battery charger and user manual
- Compact & lightweight
- One year warranty



Use with:

- Security Cameras during setup, testing, and monitoring
- DVRs, Cable & Satellite TV boxes & DVD players
- Servers, computers & laptops as a spare monitor
- DSLR cameras as a second screen while broadcasting live events
- Raspberry PI Projects and much more

Ordering Information:

HDCM-4K 7" 4K Compatible Monitor

**Hardware not included for rack mounting*



HDCM-4K 7" Ultra-Compact HD 4K Security Test Monitor

Connects using HDMI, Composite BNC-In & BNC-Out, and Component BNC

Specifications

LCD Panel	
Size	7-inch TFT LCD
Backlight Lamp	LED Backlight
Resolution	800 x 480, up to 1920 x 1080 (H x V)
Aspect Ratio	16:9
Brightness	450cd/m2
Contrast	500:1
Viewing Angle	70°/ 70°(L/R), 50°/ 50°(U/D)
Display	
Display Mode	480i/p, 576i/p, 720p (50/60Hz), 1080i/p (50/60Hz)
I/O Functions	
HDMI	1x HDMI Input
YPbPr - BNC	YPbPr Input
Video - BNC	1x Video Input
Audio - BNC	1x Audio Input
Earphone Jack	1 x 3.5mm Earphone Jack at Front Panel
Speakers	1x Built-in 1W Speaker at Front Panel
XLR DC	1x Input
Function Keys	Left, Right, Menu, Up, Down, Mode, Power
Power Supply	
Input Voltage	DC 12V or AC 100-240V
Consumption	≤6W
Mechanical Design	
Weight	1lb (0.45kg)
Dimensions	188mm x 130.7mm x 31mm