


LDEPE2270MA5N00

Aliases (DEPE2270MA5N00)

General Information

LDE, Film, Metallized PEN Stacked, Automotive Grade, 0.027 uF, 20%, 200 VAC, 630 VDC, 125°C, 2824, 4mm



Series LDE Dielectric Metallized PEN Stacked Style SMD Chip Features Automotive Grade RoHS Yes Qualifications AEC-Q200 AEC-Q200 Yes 104 Weeks Shelf Life MSL 2a

Specifications	
Capacitance	0.027 uF
Capacitance Tolerance	20%
Voltage AC	200 VAC
Voltage DC	630 VDC
Temperature Range	-55/+125°C
Rated Temperature	125°C
Dissipation Factor	0.8% 1kHz
Insulation Resistance	1GOhms
Max dV/dt	100 V/us

Click here for the 3D model.

Dimensions	
Chip Size	2824
L	7.3mm +/-0.4mm
W	6.1mm +/-0.4mm
Т	4mm MAX
В	0.4mm +0.5/-0.3mm

Packaging Specifications

Packaging	T&R
Packaging Quantity	1750

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.