ד <u></u>	т (п		0			
	ØS					
			LAYC	DUT SHOWN AS EXAMPLE		
	Keying Shown as example					
CHARACTERISTICS	Connector dimension					
-Standard : Based on MIL-DTL-38999 Series III	Dim Nomin ØS 25 Mag]
-Shell Material : Composite -Shell Plating : Olive drab Cadmium	Z' 31.5 N VV THREAD M15x1			ot be liable for any non-conformit f the Products which does not co		
-Insulator : Thermoplastic	VV HINLAD WITSAT	<u>σ</u>	the Specifications is	ssued by either of the Parties or I	by a third party	
-Contacts : Copper Alloy			(profession	nal recommendation, technical n	otice.)	
-Seals & Grommet : Silicon Elastomer				Country Jurisc	iction & Control List	
-Contact Plating : Gold over copper Alloy 0.8µm minimum		_		FR	Not Listed	
-Durability : 500 Mating cycles			PN: 8D511J22PDL			
-Delivered without Souriau contacts				N. ODJIIJZZF DL		
-Temperature Range : -65°C to +175°C		A	15-10-2016 First Release			
-Salt Spray : 2000 hours				h		MOD N°
Mass : 11.1 g ± 10%		ISS Designed	DATE Latest modification d By: Date:	- by	CUSTOMER DRAWING	MODIN
		1	TITLE Composite P		Plug 8D series	
BASIC SERIES: 8D 5 - 11 J	22 P D L	SCAL		General linear	NPRDS / PROJECT	
SHELL TYPE : Plug with RFI Shielding	Delive	ered W/O Contacts NA		Tolerances: ±	859	
CONTACT TYPE : Standard Crimp Contact					This document is the prop SOURIAU	erty of
SHELL SIZE : 11	CONTACT TYPF	: PIN(500 Matings)	URIAU WWW.S	SOURIAU.COM	it must not be reproduce communicated without per	
PLATING : J = Olive drab Cadmium		CT LAYOUT : 11-22	AT	SOURIAU DRG N°		SHEET
	CONTA	A3		8D511J22PDL-C		1/2
1			-			1//

F	Ŧ	۵	г	m		0		
		Contact Layout						
4	(00 0°						
		4#22D						
	Ctc A B C	11-22 X Y 1.905 1.905 1.905 -1.905 -1.905 -1.905						
ω	D	-1.905 1.905						
	_					the Specifications	of the Products w	
N							Count FR	
						16 First Release	N: 8D511	
					ISS DATE Designed By:	Latest modification Date:	Latest modification - by Date:	
					TITLE		Comp	
-					SCALE NA	$\bigcirc \bigcirc$	General linear Tolerances: ±	
					SOURIA	U www.	SOURIAU.	
					FORMAT		SOURIAL	

G

Н

F

Е

A3

D

С

