	т <u></u>	m	D		0		3		
4	Z'								2
ω					LAYOUT SH	OWN AS EXAMPLE			(
	Keyin	g Shown as example							
	CHARACTERISTICS	Connector dimension							
-	-Standard : Based on MIL-DTL-38999 Series III	Dim Nominal							
	-Shell Material : Composite	ØS 32.5 Max Z' 31.5 Max			SOURIAU shall not be lia				
	-Shell Plating : Nickel	VV THREAD M22x1-6g			due to a use of the Pi the Specifications issued b	roducts which does not (ov either of the Parties o			
	-Insulator : Thermoplastic					ommendation, technical			
	-Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer								
	-Contact Plating : Gold over copper Alloy 0.8µm minimum					Country Juri FR	sdiction & Control List Not Listed		
	-Durability : 500 Mating cycles					L			
	-Delivered with Souriau contacts and Accessories				PN: 8D515M05PA				
.	-Temperature Range -65°C to +200°C								_
	-Salt Spray : 2000 hours		A	19-10-2016 Fi	rst Release				
	-Mass : 21.4 g ± 10%		ISS		Latest modification - by			MOD N°	,
			Desig	ned By:	Date:		CUSTOMER DRAWIN	3	_
				TITLE		Composite Plug	8D series		
1	BASIC SERIES: 8D 5 - 15 M 05 P	A	S	CALE		eral linear	NPRDS / PROJECT		\neg
	SHELL TYPE : Plug with RFI Shielding			NA	(Ψ)	erances: ±	859		
-	CONTACT TYPE : Standard Crimp Contact				I	I	This document is the SOURIAU		\neg
-			SC	DURIAU	WWW.SOU	RIAU.COM	it must not be repr	oduced or	
-	SHELL SIZE : 15 CONTACT TYPE : PIN(500 Mati			RMAT	communicated without p				
1 1	PLATING : M = Nickel	CONTACT LAYOU	01.15-05	\3		JRIAU DRG Nʻ 515M05PA-C		SHEET	
-									

	т	۵	н п	п	D	0	
		Contact Layout $ \underbrace{}_{F} \underbrace{_{F} _{\Phi} _{B}}_{B} $					
4	-> Conta position	$\begin{array}{c} E \\ \hline \\ D \\ \hline \\ D \\ \hline \\ D \\ \hline \\ \hline \\ Contacts \\ (Insert arrangement 15-5) \\ act \\ Insert arrangement 15-5) \\ \hline \\ act \\ Insert arrangement 15-5) \\ \hline \\ \hline \\ Contacts \\ \hline \\ (Insert arrangement 15-5) \\ \hline \\ \hline \\ (In$					
		+.000 (0.00) +.100 (2.54) +.174 (4.42) +.024 (0.61) +.094 (2.39)148 (3.76) 094 (2.39)148 (3.76) 174 (4.42) +.024 (0.61)					
ى ت							
						SOURIAU shall not be lial due to a use of the Pro the Specifications issued by (professional reco	oducts wl y either o mmenda
2					A 19-10-20	PN: 8D	Count FR 0515
					ISS DATE Designed By: TITLE	Latest modification - by Date:	Compo
<u> </u>					SCALE NA	Gener Tole	ral linear rances: ±
						SOU	IRIAU
	Н	G	F	E	A3	8D5	515M
					\bigvee		

