<b>T</b>	יד וד.		0	σ	A	
4	ØS					4
ω			LAYOUT SHOW	N AS EXAMPLE		3
	Keying Shown as example					
<ul> <li>CHARACTERISTICS</li> <li>-Standard : Based on MIL-DTL-38999 Series III</li> <li>-Shell Material : Composite</li> <li>-Shell Plating : Olive drab Cadmium</li> <li>-Insulator : Thermoplastic</li> <li>-Contacts : Copper Alloy</li> <li>-Seals &amp; Grommet : Silicon Elastomer</li> <li>-Contact Plating : Gold over copper Alloy 0.8µm minimum</li> <li>-Durability : 500 Mating cycles</li> <li>-Delivered with Souriau contacts and Accessories</li> <li>-Temperature Range : -65°C to +175°C</li> </ul>	Connector dimensionDimNominalØS35.7 MaxZ'31.5 MaxVV THREADM25x1-6g	A 14-10-2016	due to a use of the Produ the Specifications issued by eit (professional recomm	for any non-conformity or dan cts which does not comply wit ther of the Parties or by a third rendation, technical notice.) Country Jurisdiction & FR Not Li	th 9 party Control List	2
-Salt Spray : 2000 hours		ISS DATE Designed By:	Latest modification - by Date:	CUST	MOD N°	°
		TITLE				
ASIC SERIES: 8D 5 - 17 SHELL TYPE : Plug with RFI Shielding	J 06 H B		General li Toleranc ±	es:	RDS / PROJECT 859	
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 17	CONTACT TYPE : PIN (15			cor	SOURIAU it must not be reproduced or nmunicated without permission	
PLATING : J = Olive drab Cadmium	CONTACT LAY	YOUT : 17-06 FORMAT A3		IAU DRG N° 17J06HB-C	SHEET	
H G	F E	D	C	В	А	

	т	۵	н П	m		0	
		Contact Layout					
4		$-x  \begin{pmatrix} \bullet & \bullet \\ \bullet & \bullet$					
		Contacts (Insert arrangement 17-6) Contact Location					
ى		position ID         X-axis (mm)         Y-axis (mm)           A         +.121 (3.07)         +.209 (5.31)           B         +.241 (6.12)         +.000 (0.00)           C         +.000 (0.00)        241 (6.12)           D        241 (6.12)         +.000 (0.00)           E        121 (3.07)         +.209 (5.31)           F         +.000 (0.00)         +.000 (0.00)					
	Shell Arrange size no. 17 -6	ment         Number of contacts         Size contacts         Service rating         Contact location         Supe service           6         12         I         All         MS2	orsedes 0053-6				
						SOURIAU shall not be liable due to a use of the Prod the Specifications issued by e (professional recom	ducts w either c
20						PN: 8D	Count FR
					A 14-10-20 ISS DATE Designed By:	016 First Release	
					SCALE	General General Toleran	
<b>_</b>					SOURIA		-
					FORMAT A3	SOUF 8D5	
	Н	G	F	I E	D	C	

