

Specification Sheet

Part Number: SNP1.25GHS0M4



Snapper Hose Clamp, .28"-.30" Bundle Diameter, PA66GF13, Black, 1000/pkg

Article Number	190-00030
Туре	SNP1.25
Color	Black (BK)
Features & Benefits	• Designed for quick, ratcheted installation and can be released and reused. • Heat stabilized material is suitable for high temperature applications.
Quantity Per	bag

	_		
Product	1100	crin	tınn
1 I Ouuct	Des	oi ip	UOII

Snapper Hose Clamps are lightweight and corrosion-resistant. Manufactured from high-performance thermoplastic materials selected to work well in a variety of diverse environments. A quick ratchet closure provides for reduced assembly line time and allows for application after connection of the hose. Release is achieved by initiating opposed lateral movement of the ratchet ends. Heat stabilized materials are available for high-temperature, motor, and under-hood applications. Snappers are also stable in a wide variety of chemicals including salts, bases, alcohols, ethers, detergents, gasoline, lubricating oils, and greases. The Snapper is available in 32 standard sizes ranging from 1/4" to 4-1/2" ID. Snappers are manufactured in white polyacetal and black polyamide 6.6 glass filled impact modified heat stabilized material. Custom designed and different colored or shaped Snappers are available based upon applications and volume requirements.

Short Description	n
--------------------------	---

Snapper Hose Clamp, .28"-.30" Bundle Diameter, PA66GF13, Black, 1000/pkg

Global Part Name

SNP1.25-PA66GF13-BK

Circation.	
Fixation	wetnoa

Plug-in mounting

Variant

Closed

Wall Thickness WT (Imperial)

.042

Wall Thickness WT (Metric)

1.111

Material

Polyamide 6.6 glass filled impact modified heat stabilized (PA66GF13%)

Material Shortcut

PA66GF13

Flammability

UL 94 HB

UV Resistant (Yes/No)

No

Operating Temperature (Metric)	-40°F to +221°F (-40°C to +105°C)
ROHS Complaint	Yes
Package Quantity(Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909988

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

 $[\]hbox{@}$ 2019 HellermannTyton. All Rights Reserved.