


RoHS Compliant




NOTES:

1. PIN ASSIGNMENT SEE TO WIRE LIST.
2. ELECTRICAL TEST CONDITION:
 - (a). 100% OPEN, SHORT & MISWIRE TEST,
 - (b). INSULATOR RESISTANCE: 10 Mohm MIN.
DC 300V 0.01sec.
 - (c). CONTACT RESISTANCE: 3ohm MAX.

Length	Part #
6 Inch	C14314-001
1 Foot	C14315-001
3 Feet	C14316-001

PIN ASSIGNMENT



4	OVERMOLD BLACK PVC 45P MA-001.	
3	USB3.1 C TYPE FEMALE BLACK INSULATOR SOLDER TYPE.	
2	USB 2.0 MALE WHITE INSULATOR SOLDER TYPE.	
1	28AWG*1P+24AWG*2C+EAB OD:4.5MM BLACK PVC JACKET UL2725 L:XXmm.	
NO.	Description	P/N

DWG NO:	PCM-0207	GOODS CODE		Draw	Jason	Date	2019/12/02
ITEM NO.		DRAWING EVIDENCE		Check		Date	
Goods NO.				Approval		Date	
Original NO.		Unit(mm)					

PREMIER CABLE MFG CO LTD

D		
C		
B		
VER.A	REVISE	Date.