

SCSI Ultra2/160/U320 LVD Cable (VHDCl68 to HD68 M/M), 3 ft. (0.91 m)

MODEL NUMBER: \$455-003



Highlights

- Short length cable for Server to i.e., Tape Loader Storage
- Premium double-shielded cable
- Meets the most current SCSI specifications for high-speed devices

System Requirements

 Any external SCSI device or host controller card requiring VHDCI68 or HD68 interface

Package Includes

 3-ft. (0.91 m) SCSI U320/U160 LVD/SE cable, VHDCl68M to HD68M

Description

Moving your network into the next phase of SCSI solutions? Look no further than Tripp Lite's brand of SCSI U320/U160 cables. Supports all legacy transfer rates including Ultra 320 . Multi-platform SCSI III external peripheral cable, VHDCI68M/HD68M. This 3-ft. (0.91 m) cable is designed to connect two SCSI III (fast and wide) or SCSI II devices together. Manufactured using double shielded 34 twisted pair high impedance cable. Constructed with low-capacitance, impedance matched, 28 AWG, stranded, tinned copper cable with insulated in polypropylene.

Features

- Supports all SCSI transfer rates through 320Mbps
- LVD/SE compliant
- Backwards compatibility with previous SCSI generations
- Double shielded (foil and braid)
- All Tripp Lite SCSI products, regardless of the SCSI generation, meet the latest specifications of ANSI
- Tripp Lite offers a complete line of internal and external solutions for SCSI/RAID and fibre channel ranging from the very latest Ultra 320 to legacy SCSI-1 and every combination in between

Specifications

OVERVIEW	
UPC Code	037332138187
Technology	SCSI
PHYSICAL	
Color	Black
Cable Jacket Color	Black



3	
0.91	
0.50 x 6.00 x 6.00	
1.27 x 15.24 x 15.24	
0.40	
0.18	
CONNECTIONS	
VHDCI68 (MALE)	
HD68 (MALE)	
WARRANTY & SUPPORT	
Lifetime limited warranty	



© 2022 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are the property of their respective owners.