

ATGBICS 331-5274-C network transceiver module Fiber optic 10000 Mbit/s SFP+ 850 nm

Brand : ATGBICS

Product code: 331-5274-C

Product name : 331-5274-C

Dell Compatible Transceiver SFP+ 10GBase-SR 850nm MMF 300m DOM

ATGBICS 331-5274-C network transceiver module Fiber optic 10000 Mbit/s SFP+ 850 nm:

ATGBICS 331-5274 10GBase-SR supports a distance of up to 300m over multi-mode fibre (MMF) using a wavelength of 850nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product is built to the exact specification of Dell 331-5274= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.

ATGBICS 331-5274-C. SFP transceiver type: Fiber optic, Maximum data transfer rate: 10000 Mbit/s, Interface type: SFP+. Product colour: Silver, Housing material: Metal, Country of origin: United Kingdom. Input voltage: 3.3 V, Maximum voltage: 3.5 V, Power consumption (typical): 1 W. Width: 13.4 mm, Depth: 56.5 mm, Height: 8.5 mm. Number of products included: 1 pc(s), Package type: Box

Performance		Features	
SFP transceiver type *Fiber opticMaximum data transfer rate *10000 Mbit/sInterface type *SFP+Single-mode fiber (SMF) supportedXMulti-mode fiber (MMF) supportedICFiber optic connectorLCSFP transceiver standardSRMaximum transfer distance300 m	•	Country of origin Brand compatibility	United Kingdom Dell
	× ✓ LC	Power Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 1 W
	avelength 850 nm hernet LAN \checkmark hernet interface type 10 Gigabit Ethernet gital Diagnostics Monitoring DM)	Operational conditions	
Wavelength Ethernet LAN Ethernet interface type Digital Diagnostics Monitoring (DDM)		Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	70 °C 0 - 70 °C -40 - 85 °C 0 - 95% 0 - 95%
Wavelength-division multiplexing (WDM)	×	Weight & dimensions	
FeaturesProduct colourSilverHousing materialMetalPlug and PlayImage: All the second secon		Width Depth Height Weight	13.4 mm 56.5 mm 8.5 mm 19 g
		Packaging data	5
		Number of products included Package type	1 pc(s) Box
		Technical details	
		Sustainability certificates	RoHS







Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.