


Trim frame



For horizontal mounting kit

To conceal the front sections of the horizontal mounting kit.

Material:
Aluminum, anodized

U horizontal	HP	Order No.	
		For 3 U sub racks	For 4 U sub racks
6	56	3685.783	3685.785
9	84	3685.784	3685.786

! Also required:

Collar screws and plastic collars, packs of 100 sets, order no. 3658.160, see page 164

Trim frame, vented



For horizontal mounting kit

To conceal the front sections of the horizontal mounting kit.

Material:
Aluminum

Surface finish:
Anodized, clear-chromated (EMC version)

Supply includes:
EMC accessories (with EMC version).

EMC

U horizontal	HP	Order No.	
		For 3 U sub racks	For 4 U sub racks
6	63	3685.787	3685.788

! Also required:

Collar screws and plastic collars, packs of 100 sets, order no. 3658.160, see page 164

EMC version

U horizontal	HP	Order No.	
		For 3 U sub racks	For 4 U sub racks
6	63	3685.291	3685.292

! Also required:

Centering screws, packs of 100, order no. 3687.050, see page 165

Plastic guide rails



For 160, 220 and 280 mm PCBs up to 2 mm nominal thickness.

2 versions are available:

- Snap-in fastening and screw-fastening
- Snap-in fastening

Material:
Polycarbonate, base material to UL 94-V0

PCB depth mm	Packs of	Order No.	
		snap-in/screw fastening1)	snap-in fastening
100	1	–	3688.005
160	1	3684.657	3684.654
220	1	3684.658	3684.655
280	1	3684.659	3684.656

! Also required:

1) Assembly screws, packs of 100, order no. 3654.360, see page 164

Plastic guide rails



For contact spring fitting

For 160, 220 and 280 mm PCBs up to 2 mm nominal thickness. By installing contact springs, an electrical connection can be made between the PCB and the assembly.

Material:
Polycarbonate, base material to UL 94-V0

PCB depth mm	Packs of	Order No.
160	1	3684.660
220	1	3684.661
280	1	3684.662

+ Accessories:

Contact springs, see page 120