4840, solder terminal, Socket, 5.9 mm, 2-pole, DC Plug/Socket



See below:

Approvals and Compliances

Description

- Solder terminal : Screw-on mounting, from rear-side
- Low Voltage DC Plug and Socket
- DC Plug: 2-pole, straight

Technical Data

Diameter	5.9 mm / 3.0 mm / 1.05 mm	
Number of Poles	2-pole	
Ratings DC	2A / 13.5VDC	
Dielectric Strength	500 VDC	
Insulation Resistance	> 100 MΩ @ 500 VDC	

Allowable Operation Tempe-	-20°C to 70°C	
rature		
Terminal	solder terminal silver plated	
Mounting	Screw-on mounting wall thickness max. 3.0 mm	
Style	straight	
Lifetime	5000 Insertions	

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals


SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.


Compliances


The product complies with following Guide Lines

Identification	Details	Initiator	Description
RoHS	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/836
©	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.


Dimensions [mm]







Diagrams





All Variants

Product group	Diameter [mm]	Number of Poles	Terminal	Order Number
DC Plug/Socket	5.9	2-pole	solder terminal	4840.2220

 $A \textit{vailability} for \textit{all} \textit{products} \textit{can} \textit{be} \textit{searched} \textit{real-time:} \textit{https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER} \textit{all} \textit{products} \textit{can} \textit{be} \textit{searched} \textit{real-time:} \textit{https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER} \textit{all} \textit{products} \textit{can} \textit{be} \textit{searched} \textit{real-time:} \textit{https://www.schurter.com/en/Stock-Check-Stock-Check-SCHURTER} \textit{all} \textit{products} \textit{can} \textit{be} \textit{searched} \textit{real-time:} \textit{https://www.schurter.com/en/Stock-Check-SCHURTER} \textit{all} \textit{products} \textit{can} \textit{be} \textit{searched} \textit{real-time:} \textit{https://www.schurter.com/en/Stock-Check-Schurter.com/en/Sto$

Packaging unit

250 Pcs

Mating Inlets/Plugs

Category / Description

DC Plug/Socket Overview complete



4840, solder terminal, Plug, 5.5 mm, 2-pole, DC Plug/Socket	4840.1220
4840, Cable, Plug, 5.5 mm, 2-pole, DC Plug/Socket	4840.5220
4840, Cable, Plug, 5.5 mm, 2-pole, DC Plug/Socket	4840.5221

DC Plug/Socket further types to 4840.2220