

NOTES: MATERIAL: HOUSING: THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED SHELL: COPPER ALLOY, GOLD FLASH PLATED CONTACT: **OPERATING TEMPERATURE:** -55°C ~ 125°C 40A (CURRENT) POWER/CO-AX CONTACT RATING: (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX. O


.XX ±0.13 .XXX ±0.05

۲ \frown \cap 20.33

INSULATOR RESISTANCE: 5000MΩ min.

DIELECTRIC WITHSTANDING VOLTAGE:

1000V AC rms



	COMBINATION D-SUB		SW REFERENCE NO.: 629 COMBO ASSEMBLY		
			DRAWN: C.B	DATE: JAN. 01/20	19
			CHECKED:	DATE:	
то	EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INCAND	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2
IVES NCY.	YOUR CONNECTION TO QUALITY & SERVICE	SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWING NUMBER: 629-21W4250-4TD		ISSUE
			PART NUMBER: 629-21W	4250-4TD	1



10.67

THIS SERIES FULLY CONFORMS T THE EUROPEAN UNION DIRECTIV 2011/65/EU FOR RoHS COMPLIANC

