		D	0	∞ >		]
A Z Z Z Z Z Z Z Z Z Z Z Z Z						4
			LAYOUT SHOWN AS EXAM	MPLE		3
	Keying Shown as example					
CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal					
<ul> <li>Shell Material : Aluminium</li> <li>Shell Plating : Olive drab Cadmium</li> <li>Insulator : Thermoplastic</li> <li>Contacts : Copper Alloy</li> <li>Seals &amp; Grommet : Silicon Elastomer</li> <li>Contact Plating : Gold over copper Alloy 0.8µm minimum</li> </ul>	ØS29.4 MaxZ31 MaxVV THREADM18x1-6g		SOURIAU shall not be liable for any no due to a use of the Products which the Specifications issued by either of the (professional recommendation Country FR	does not comply with e Parties or by a third party		2
-Durability : 500 Mating cycles -Delivered without Souriau contacts			PN: 8D513W9			
-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours		A 19-10-2016	First Release			_
		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°	-
		TITLE	Aluminiu	m Plug 8D series		_
→ BASIC SERIES: 8D 5 - 13 W → SHELL TYPE : Plug with RFI Shielding	98 S N L Delivered W/O Contacts	SCALE -	General linear Tolerances:	NPRDS / PROJECT <b>859</b>		_
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 13	ORIENTATION : N       SOURIAU       This document is the property of SOURIAU.         CONTACT TYPE : SOCKET(500 Matings)       SOURIAU       This document is the property of SOURIAU.					
PLATING : W = Olive drab Cadmium	CONTACT LAYOUT : 13-98		SOURIAU D		SHEET	_
		A3	8D513W98		1/2	

ſ	<b></b>	۵	н <b>г</b>	m	D	0
		Contact Layout				
4		$ \begin{array}{c} \bullet \\ & \bullet \\ $				
	Cont positic A B B C C C C C C C C C C C C C C C C C	on ID         (mm)         (mm)           A         +.000 (0.00)         +.195 (4.95)           B         +.125 (3.18)         +.150 (3.81)           C         +.139 (4.90)         +.030 (0.76)           D        164 (4.17)        105 (2.67)           E         +.000 (0.00)        135 (3.43)           C        184 (4.17)        105 (2.67)           A        125 (3.18)         +.030 (0.76)           H        125 (3.18)         +.150 (3.81)           H        125 (3.18)         +.150 (3.81)           H         +.026 (1.65)        015 (0.38)				
ယ	Shell Arrangement No. c	Number Size Service Contact Supersedes oritacts 10 20 I All MS20051-98				
	I					
	Γ					SOURIAU shall not be liable for ar due to a use of the Products w the Specifications issued by either o (professional recommenda
N						Count FR
						PN: 8D513V
					A 19-10-20	116 First Release
					ISS DATE	
					Designed By:	Date:
					TITLE	Alumir
<u> </u>					SCALE	General linear Tolerances:
					SOURIA	U WWW.SOURIAU.
					FORMAT	SOURIAL
		1	I		A3	8D513W
	Н	G	F F	E	D	C

	σ		L 1	>		
						4
						3
whic r of t datio	non-conformit h does not co he Parties or t n, technical n	mply wi by a thire otice.)	th d party			
intry R	Jurisd	liction & Not Li	Control List sted			2
W	98SNL					
		CUST			MOD N°	
CUSTOMER DRAWING						
ninium Plug 8D series						
ır	NPRDS / PROJECT					
			859			1
.CC	.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission					
	DRG N°	L			SHEET	1
<u>v9</u>	8SNL-C		-		2/2	J
	В		/	A Contraction		