[	т <u> </u>		0	₿ 2	
4					
ω			LAYOUT SHOWN AS EXAM	PLE	
	Keying Shown as example				
	CHARACTERISTICS       Connector dimension         -Standard : Based on MIL-DTL-38999 Series III       Dim       Nominal				
N	Shell Material: AluminiumØS35.7 Max-Shell Plating: Olive drab CadmiumZ31 Max-Shell Plating: Olive drab CadmiumVV THREADM25x1-6g-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer-Contact Plating: Gold over copper Alloy 0.8µm minimum	SOURIAU shall not be liable for any non-conformity or damage         due to a use of the Products which does not comply with         the Specifications issued by either of the Parties or by a third party         (professional recommendation, technical notice.)         Country       Jurisdiction & Control List         FR       Not Listed			
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories PN: 8D517W20AC			0AC		
	-Temperature Range: -65°C to +175°C-Salt Spray: 500 hours	A 17-10-201 ISS DATE	.6 First Release Latest modification - by		MOD N°
		Designed By:	Date:	CUSTOMER DRAWING	
		TITLE	Aluminiun	n Plug 8D series	
_	BASIC SERIES:     8D     5     -     17     W     20     A     C       SHELL TYPE     : Plug with RFI Shielding     -     -     17     W     20     A     C	SCALE	General linear Tolerances:	NPRDS / PROJECT <b>859</b>	
	CONTACT TYPE     : Standard Crimp Contact       SHELL SIZE : 17     CONTACT TYPE : PIN(500 Matings)	SUURIAL	J WWW.SOURIAU.COM	This document is the proper SOURIAU it must not be reproduced communicated without perm	lor
	PLATING : W = Olive drab Cadmium     CONTACT LAYOUT : 17-20	FORMAT	SOURIAU DI		SHEET
		A3	8D517W20		1/2

12       -8.05       -1.4         13       -8.05       1.4         14       -7.11       4.03         15       -4.29       4.29         16       -4.16       7.06         ISS DATE Latest modification - by         Designed By:       Date:								
20* 4 # 12 16 # 22D		Ŧ	۵	ц т	т	D	0	
SOURAU shall not be liable for a latest modification by beinged by the general model           Image: Source of the state of	4		Contact Layout 20*					
Co Citic X Y T A 00 5.51 B 3.17 0 C 0 -5.51 D 3.17 0 1 4.16 7.06 2 4.29 4.29 3 7.11 4.03 7 4.29 4.29 8 4.16 7.06 9 4.16 7.06 9 4.16 7.06 10 4.29 4.29 11 7.11 4.03 12 8.05 1.4 13 8.05 1.4 13 8.05 1.4 13 8.05 1.4 13 8.05 1.4 13 8.05 1.4 13 8.05 1.4 14 7.11 4.03 15 4.29 4.29 16 4.16 7.06 X M M M M M M M M M M M M M			16#22D					
Co Co Co Co Co Co Co Co Co Co			17-20					
B         3.17         0           D         -3.17         0           1         4.16         7.06           2         4.29         4.29           3         7.11         4.03           4         8.05         1.4           6         7.11         4.03           4         8.05         1.4           6         7.11         4.03           7         4.29         4.23           8         4.16         -7.06           10         -4.23         4.29           11         -7.11         4.03           12         -8.05         1.4           13         -8.05         1.4           14         -7.11         4.03           15         -4.29         4.29           16         -4.16         7.06				-				
C 0 0 -5.51 D -3.17 0 1 4.16 7.06 2 4.29 4.29 3 7.11 4.03 4 8.05 1.4 6 7.11 4.03 7 4.29 4.29 8 4.16 7.06 9 -4.16 7.06 10 -4.29 -4.29 11 -7.11 -4.03 12 -8.05 1.4 13 -8.05 1.4 13 -8.05 1.4 14 -7.11 4.03 15 -4.29 4.29 16 -4.16 7.06 Na trianel for the specification such by the specification such by the specification is such the specificati			+ + + + + + + + + + + + + + + + + + + +	-				
0         3.17         0           1         4.16         7.06           2         4.29         4.29           3         7.11         4.03           4         8.05         1.4           6         7.11         -4.03           7         4.29         -4.29           8         4.16         -7.06           9         -4.16         -7.06           11         -7.11         -4.03           12         -8.05         -1.4           14         -7.11         -4.03           12         -8.05         -1.4           14         -7.11         4.03           15         -4.29         4.29           16         -4.16         7.06           18         -8.05         -1.4           14         -7.11         4.03           15         -4.29         4.29           16         -4.16         7.06           18         DATE         Latestmodification by           Detignet by         Date:           116         -4.16         7.06				-				
1       4.16       7.06         2       4.29       4.29         3       7.11       4.03         4       8.05       1.4         5       8.05       1.4         6       7.11       4.03         7       4.29       4.29         8       4.16       -7.06         10       -4.29       4.29         11       -7.11       -4.03         12       -8.05       1.4         14       -7.11       4.03         15       -4.29       4.29         16       -4.16       7.06         N: 8D517         Na       Designed By:       Dete:         TTLE       Alum         SOURIAU       SOURIAU         SOURIAU       MWW.SOURIAU         A3       SOURIAU				-				
2       4.29       4.29         3       7.11       4.03         4       8.05       1.4         5       8.05       -1.4         6       7.11       -4.03         7       4.29       -4.29         8       4.16       -7.06         9       -4.16       -7.06         10       -4.29       -4.29         11       -7.11       -4.03         12       -8.05       -1.4         13       -8.05       1.4         14       -7.11       4.03         15       -4.29       4.29         16       -4.16       7.06	ယ			-				
3       7.11       4.03         4       8.05       1.4         6       7.11       -4.03         7       4.29       -4.29         8       4.16       -7.06         9       -4.16       -7.06         10       -4.29       -4.29         11       -7.11       -4.03         12       -8.05       1.4         13       -8.05       1.4         14       -7.11       4.03         15       -4.29       -4.29         16       -4.16       7.06         N B517         Note::::::::::::::::::::::::::::::::::::				-				
4       8.05       1.4         5       8.05       -1.4         6       7.11       -4.03         7       4.29       -4.29         8       4.16       -7.06         9       -4.16       -7.06         10       -4.29       -4.29         11       -7.11       -4.03         12       -8.05       -1.4         13       -8.05       1.4         14       -7.11       4.03         15       -4.29       4.29         16       -4.16       7.06				-				
S         8.05         -1.4           6         7.11         -4.03           7         4.29         -4.29           8         4.16         -7.06           9         -4.16         -7.06           10         -4.29         -4.29           11         -7.11         -4.03           12         -8.05         -1.4           13         -8.05         1.4           14         -7.11         4.03           15         -4.29         4.29           16         -4.16         7.06				-				
6       7.11       -4.03         7       4.29       -4.29         8       4.16       -7.06         9       -4.16       -7.06         10       -4.29       -4.29         11       -7.11       -4.03         12       -8.05       -1.4         13       -8.05       1.4         14       -7.11       4.03         15       -4.29       4.29         16       -4.16       7.06         A.25         14       -7.11         4.03       -7.06         A.29         16       -4.16         7.06       -4.29         A.27         SOURIAU Shall not be liable for:         11       -7.11         -7.06       -7.06         A.29         16       -4.16         Deligned Br:         Deligned Br:         Deligned Br:         Deligned Br:         Deligned Br:         SOURIAU         NA       Mail         SOURIAU         A3<								
7       4.29       -4.29         8       4.16       -7.06         9       -4.16       -7.06         10       -4.29       -4.29         11       -7.11       -4.03         12       -8.05       -1.4         13       -8.05       1.4         14       -7.11       4.03         15       -4.29       4.29         16       -4.16       7.06         N 80517         15       -4.29       4.29         16       -4.16       7.06			+	-				
8       4.16       -7.06         9       -4.16       -7.06         10       -4.29       -4.29         11       -7.11       -4.03         12       -8.05       -1.4         13       -8.05       1.4         14       -7.11       4.03         15       -4.29       4.29         16       -4.16       7.06             Na       PN: 8D517             Version       Sourcial             Sourcial       Sourcial		7					SOURIAU shall not be lia	ble for any non-
10       -4.29       -4.29       -4.29       -1.1		8	4.16 -7.06				due to a use of the Pr	oducts which do
10       -4.2.9       -4.2.9         11       -7.11       -4.03         12       -8.05       -1.4         13       -8.05       1.4         14       -7.11       4.03         15       -4.29       4.29         16       -4.16       7.06         A         ITTLE         NA         SOURIAU         WWW.SOURIAU.         FORMAT         SOURIAU         FORMAT         SOURIAU		9	-4.16 -7.06					
12       -8.05       -1.4         13       -8.05       1.4         14       -7.11       4.03         15       -4.29       4.29         16       -4.16       7.06         A 17-10-2016 First Release         ISS DATE Latest modification - by         Designed By:       Date:         TITLE         NA       A         SCALE       General linear         NA       E         SOURIAU       WWW.SOURIAU.         FORMAT       SOURIAU         RA       SOURIAU				-			(professional reco	
13       -8.05       1.4         14       -7.11       4.03         15       -4.29       4.29         16       -4.16       7.06         A       17-10-2016       First Release         ISS       DATE       Latest modification - by         Designed By:       Date:         TITLE       Alum         SCALE       TITLE         NA       Image: Scale         5       SOURIAU         WWW.SOURIAU.         FORMAT       SOURIAU         A3       SDURIAU				_				Country
14       -7.11       4.03         15       -4.29       4.29         16       -4.16       7.06         A       17-10-2016       First Release         ISS       DATE       Latest modification - by         Designed By:       Date:         TITLE       Alum         SCALE       General linear         NA       Image: SCALE         NA       Image: SCALE         SOURIAU       WWW.SOURIAU.         FORMAT       SOURIAU         SOURIAU       SOURIAU	N			4				FR
15       -4.29       4.29         16       -4.16       7.06         A       17-10-2016       First Release         ISS       DATE       Latest modification - by         Designed By:       Date:         SCALE       Ceneral linear Tolerances:         NA       Image: SCALE         NA       Image:				-				
16       -4.16       7.06         ISS       DATE       Latest modification - by         Designed By:       Date:         ITTLE       Alum         SCALE       Image: SCALE         NA       Image: SCALE         SOURIAU       WWW.SOURIAU         FORMAT       SOURIAU         FORMAT       SOURIAU				-			PIN. OL	51/ 2020
ISS DATE Latest modification - by Designed By: Date: TITLE Alum SCALE ALUM				-		A 17 10 20	1C First Delegas	
Designed By:     Date:       TITLE     Alum       SCALE     Image: SCALE       NA     Image: Scale       NA     Image: Scale       SOURIAU     WWW.SOURIAU.       FORMAT     SOURIAU       A3     8D517V		10	-4.10 7.00			A 17-10-20		
TITLE     Alum       SCALE     General linear       NA     Image: Description of the second seco								
SCALE NA SOURIAU FORMAT A3 SOURIAU SOURIAU SOURIAU A3 SOURIAU SOURIAU						Designed By.	Date.	
NA Tolerances: ± SOURIAU WWW.SOURIAU. FORMAT SOURIA A3 8D517V								Aluminium
FORMAT SOURIA A3 8D517V	<u> </u>						-[	rances:
A3 8D517V						SOURIA	U WWW.SOUF	RIAU.COM
A3 8D517V						FORMAT		חרו אוםו
H I G I F I E V D I C I					_	1		
		Н	G		E		C	

	B		A		_
					4
					3
whic r of t datio ntry R	on, technical n	mply with by a third party			2
		CUSTOMER	DRAWING	MOD N°	<u> </u>
inium Plug 8D series					
r NPRDS / PROJECT					
859					
.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission					
UI	DRG N°			SHEET	
	OAC-C			2/2	
/			1	,	